

SIMULATION OF MAJOR PARAMETERS FOR LIQUID PIPELINES

A Project Work
Submitted in the Partial Fulfillment of the Requirements
For the Degree of

MASTER OF TECHNOLOGY
IN
PIPELINE ENGINEERING

Under the Guidance of

Internal

Dr. D.N.SARAF

Distinguished Professor
College of engineering
University of Petroleum and Energy Studies


External

Mr. ASWANI SONI

Assistant General Manager
Pipelines Engineering
Engineers India Limited


BY

JAYARAJ.PG
ROLL No: R160205005



UNIVERSITY OF PETROLEUM AND ENERGY STUDIES
DEHRADUN

MAY -2007



इंजीनियर्स
इंडिया लिमिटेड



ENGINEERS
INDIA LIMITED

पंजीकृत कार्यालय: इंजीनियर्स इंडिया भवन, 1, भीकाएजी कामा प्लेस, नई दिल्ली-110066
Regd. Office: Engineers India Bhawan, 1, Bhikaiji Cama Place, New Delhi-110066

TRG/VT/2007 (S)/3

April 30, 2007

TO WHOMSOEVER IT MAY CONCERN

This is to certify that **Mr. P.G. Jayaraj**, a student of M.Tech (Pipelines Engineering) from University of Petroleum & Energy Studies, Dehradun, completed his Practical Training in Engineering – Pipelines Department of our organization from March 06, 2007 to April 27, 2007. He has undertaken his training assignment on “Simulation of Major Parameters for Liquid Pipelines.”

During the course of training, **Mr. P.G. Jayaraj** has been regular and punctual. He has shown interest in his assignment and his performance on evaluation has been found to be “Very Good.”

(Handwritten signature of R.P. Goswami)

(R.P. Goswami)

Asst. General Manager – Human Resource

सर्व शिक्षा अभियान

उत्कृष्टता का आधार – हमारे कर्म

DELIVERING EXCELLENCE THROUGH PEOPLE

फोन : 26102121 (EPABX)

फैक्स/Fax: 91-11-26186245

Phone : 26101419 (DISA)

Visit us at <http://www.engineersindia.com>



हिन्दी देश की एकता की कड़ी है।



UNIVERSITY OF PETROLEUM & ENERGY STUDIES

CERTIFICATE

This to certify that the work contained in this thesis entitled “**SIMULATION OF MAJOR PARAMETERS FOR LIQUID PIPELINES**” has been carried out by **Jayaraj.PG** under the supervision of Mr. Aswani Soni, AGM, Pipelines Engineering Division, Engineers India Limited, New Delhi and myself. That this work has not been submitted elsewhere for a degree.

14.05.07

Dr. D N Saraf,

Distinguished professor,
College of Engineering,
University of Petroleum and Energy Studies,
Dehradun – 248007.

Corporate Office :

Hydrocarbons Education & Research Society
3rd Floor, PHD House 4/2, Siri Institutional Area
August Kranti Marg, New Delhi-11001 India
Ph + 91-11-41730151-53 Fax +91-11 1730154

Main Campus :

Energy Acres, PO Bidholi, Via Prem Nagar,
Dehradun-248 007 (Uttaranchal) India
Ph. : +91-135-2261090-91, 2694201/203/208
Fax : +91-135-2694204

Regional Centre (NCR) :


SCO 9-12, Sector-14, Gurgaon 122 007
(Haryana), India
Ph : + 91-124-4540300
Fax : +91 124 4540 330



UNIVERSITY OF PETROLEUM & ENERGY STUDIES

CERTIFICATE

This to certify that the project work entitled on “SIMULATION OF MAJOR PARAMETERS FOR LIQUID PIPELINES” submitted by **Jayaraj.PG** in partial fulfillment of the requirement for the degree of Masters of Technology in Pipeline Engineering, at College of Engineering, University of Petroleum and Energy Studies, Dehradun is a record of the work carried out by him.


17.05.07

Dr.B.P.Pandey,
Dean,
College of Engineering.

Corporate Office :
Hydrocarbons Education & Research Society
Floor, PHD House. 4/2, Siri Institutional Area
Anand Kranti Marg, New Delhi-11001 India
+ 91-11-41730151-53 Fax : +91-11 1730154

Main Campus :
Energy Acres, PO Bidholi, Via Prem Nagar,
Dehradun-248 007 (Uttaranchal) India
Ph. : +91-135-2261090-91, 2694201/203/208
Fax : +91-135-2694204

Regional Centre (NCR) :
SCO 9-12, Sector-14, Gurgaon 122 007
(Haryana), India
Ph . + 91-124-4540300
Fax . +91 124 4540 330

E-mail : info@upes.ac.in URL www.upes.ac.in

ACKNOWLEDGEMENT

This is to acknowledge with thanks to the management of Engineers India Limited for giving me an opportunity to pursue my project and in particular Mr. A. Soni (AGM, Pipelines Engineering), Ashok singh (Senior Engineer, Process Engineering) for their able guidance and support.

I have no words to express the help, guidance and support that I had received during my project from Dr. D.N.Saraf, distinguished Professor College of engineering, UPES, Dehradun, for the completion of project.

I must also thank, Mr. R.P. Shriwas, Course Coordinator, Pipeline Engineering, UPES, Dehradun, Mr. Anupam Das, Mr. Manoj.K.Malhotra, and Mr. D.S.Kaura from Engineers India Limited for their valuable support and also a great thank for the support provided by my parents and friends.

Jayaraj. ujj.
17.05.07.

JAYARAJ.PG

M.Tech (Pipeline Engineering),
University of Petroleum and Energy Studies,
Dehradun.

CONTENT

	ABSTRACT	i
CHAPTER: 1	INTRODUCTION	
1.1	INTRODUCTION ABOUT THE PROJECT	01
CHAPTER: 2	PROPOSED PIPELINE DESIGN SPECIFICATION	
2.1	DESIGN CODES AND STANDARDS	02
2.2	PIPELINE SCHEMATIC MAPS	03
2.3	DESIGN DATA	04
CHAPTER: 3	ENGINEERING DESIGN BASIS	
3.1	BORL PIPELINE	05
3.2	PIPELINE WALL THICKNESS ANALYSIS	05
3.3	HORIZONTAL DIRECTIONAL DRILLING	09
3.4	VALVES	10
3.5	PIPING	11
3.6	SCRAPER STATIONS	12
3.7	WELDING	13
3.8	CROSSINGS	13
3.9	EXTERNAL/ INTERNAL CORROSION COATING	14
3.10	HYDROSTATIC TESTING	15
CHAPTER: 4	PROCESS DESIGN BASES	
4.1	BATTERY LIMITS	16
4.2	PIPELINE PARAMETERS	16
4.3	ELEVATIONS	17
4.4	UTILITIES	17
4.5	INSTRUMENTATION AND CONTROL	18
4.6	METERING	18
4.7	TEMPERATURES	19
4.8	PUMPS	19
4.9	CRUDE CHARACTERISTICS	20
4.10	SECTIONALIZING VALVE STATIONS	20

CHAPTER: 5	SIMULATIONS	
5.1	STEADY STATE Vs TRANSIENT SIMULATION	22
5.2	CHOOSING THE SIMULATION TIMETABLE	23
5.3	TLNET APPLICATIONS	23
5.4	LEGS	25
5.5	TRANSIENT ANALYSIS APPLICATION	25
5.6	STEPS INVOLVED IN SIMULATION	26
5.7	SIMULATION INPUT AND OUTPUT	28
CHAPTER: 6	CONCLUSIONS	
6.1	GRAPHICAL ANALYSIS	66
6.2	FOR OPTIMISATION	66
	REFENCES	68
	ANNEXEURE	69

ABSTRACT

M/s Bharath Oman Refinery Limited (BORL) proposes to lay crude oil pipeline from Vadinar a sea part to Bina, where a refinery is proposed to be built. The initial part in the report includes proposed pipeline design specification datas. The following part includes engineering and process design basis calculations. The major part is simulation of crude pipeline using Transient Liquid Net Analysis (TLNET), in which steady and transient state is made to simulate the pipeline surge relief, also to determine the maximum throughput, from the simulated results the operating costs can be reduced. TLNET calculates pressure, density and velocity at every knot. Spacing calculation for booster pump station and simulation of surge relief valve with respect to result obtained from the simulation and also suggestion for optimisation from the output is also carried out at the result.

CHAPTER 1

INTRODUCTION

1.1 About The Project:

M/s Bharath Oman Refinery Limited (BORL) propose to lay crude oil pipeline from Vadinar a sea part to Bina, where a refinery is proposed to be built. The initial part in the report includes proposed pipeline design specification datas. The following part includes engineering and process design basis calculations. The major part is simulation of crude pipeline using Transient Liquid Net Analysis (TLNET), in which steady and transient state is made to simulate the pipeline surge relief, also to determine the maximum throughput, by the simulated the operating costs results can be reduced. TLNET calculates pressure, density and velocity at every knot.

Input parameters such as equipment parameters, equipment set point ramp schedule for block valve at the terminals. Other input datas such as bulk modulus, coefficient of thermal expansion, heat capacity, kinematic viscosity and inlet fluid conditions. Forming of network is one of the major parts before simulation. Legs are formed for the whole section of the line, from that the initial and tail nodes are determined. Apart from this the valve physical characteristic data, external regulator data, number of single pumps, number of nodes, elevation profile data. Work carried out by myself is datas gathering and calculation for engineering and process design basis the input of simulation part. Suggestion for optimisation from the output is also carried out at the end.

The subsequent pages contain the details about M/s Bharat Oman Refinery Limited Pipeline Project from Vadinar to Bina pipe wall thickness calculation, basic process data for the project, spacing calculation for booster pump station and simulation of surge relief valve with respect to EIL data and project data.

CHAPTER: 2

PROPOSED PIPELINE DESIGN SPECIFICATION

Introduction:

M/s Bharath Oman Refinery Limited (BORL) propose to lay crude oil pipeline from Vadinar a sea part to Bina, where a refinery is proposed to be built. The pipeline is proposed to pass through Sidhasar, Thamina, Bewari and Sanadavata [6]. A geographical route map is shown in Figure: 1.

This project deals with the basic mechanical, process calculation and simulation for spacing the booster pump station.

2.1 Design Codes and Standards:

ASME B 31.4	Liquid Hydrocarbons Transmission Systems
ASME B 31.3	Process Piping
OISD Std. 138	Inspection of Cross Country Pipelines-Onshore
API Std. 1102	Steel Pipeline Crossing Railways & Highways
API Std. 1104	Standard for Welding Pipelines and Related Facilities

Pipelines and terminal facilities envisaged shall be designed and engineered primarily in accordance with the provisions of the latest edition of Code ASME B 31.4: Liquid Hydrocarbons Transmission Systems and OISD 141: Design and Construction Requirements for Cross Country Hydrocarbon Pipelines. In addition, requirements, as applicable to liquid service of following codes/standards shall be complied with Pipeline transportation systems. In case of conflict between the requirements of ASME B 31.4/OISD 141 and other codes/Standards referred above, requirement of ASME B 31.4/OISD 141 shall govern.

2.2 Pipeline Schematic Maps:

Taking the various factors essential for route selection, the route is selected. The route map is shown in Figure: 1.




Figure: 1 Map showing pipeline route from Vadinar to Bina.

2.3 Design Data:

Pipeline design shall be designed for conditions as given in Table: 1.

Table: 1 Pipeline Design Parameters.

Pipeline Design Parameters	
Description	Value
Main line OD	610 mm (24")
Length	935Km
No. of river crossings (width>100 m)	30
Products: Crude Oil	
Design Pressure (kg/cm ² g)	70.1
Operating Pressure (kg/cm ² g)	63.7
Max. Design Temperature, °C	
Above ground section	-29 to 65
Under ground section	-29 to 45
Operating temperature, °C	22 – 25
Economic Design Life, years	35
Corrosion Allowance, mm	1

CHAPTER 3

ENGINEERING DESIGN BASIS

3.1 BORL PIPELINE [6]:

Pipeline shall be designed in accordance with requirements of ASME B 31.4 and OISD 141. The pipeline shall withstand all installation, testing and operating condition/ loads. All necessary calculations shall be carried out to verify structural integrity and stability of the pipeline for the combined effect of pressure, temperature, bending (elastic), soil/pipe interaction, external loads and other environmental parameters as applicable during all phases of work from installation to operation. Allowable stress limit shall be as per ASME B 31.4. Such calculations shall include, but are not limited to following:

Buoyancy control and stability analysis for pipeline section to be installed in areas subjected to flooding/submergence. Unless specified, specific gravity of installation in such area shall be at least 1.2.

- Stress analysis at crossing of major rivers, rail and highway etc.
- Crossing analysis of rivers by Horizontal Directional Drilling (HDD) as applicable.
- Pipeline expansion and its effect on station piping (above ground/below ground).

The area through which pipeline goes have been divided into different classes depending upon many factors such as the population density etc and thus a change in class changes the design factor for that particular area.

3.2 Pipeline Wall Thickness Analysis [1, 3]:

The calculation of pipeline wall thickness is as per ASME Code B 31.4 for the onshore liquid pipeline. As per ASME B 31.4 wall thickness for a straight pipe under internal pressure is given by the following expression:

PD

$$t = \frac{PD}{2SE} \rightarrow (1)$$

2D.F.SYMS

where,

P = Pipeline design pressure in psi,

S = Specified Minimum Yield Strength (SMYS) in psi,

t = Nominal wall thickness in mm,

D = Pipe outside diameter in mm,

F = Design factor obtained from ASME B 31.4

E = Longitudinal joint factor obtained from Table: 2

Line pipe shall conform to API 5L and Company specifications. Type of line pipe to be used shall be LSAW/ HSAW. Line pipe size, material grade shall be 24” (610 mm) OD, API 5L Gr. X-70 and wall thickness shall be 7.1/7.9/11.9 mm for various places [2, 3, 4].

Table: 2 E Factor for Various Classes of Pipes.

Spec. No.	Pipe class	E factor
ASTM A 53	Seam Less	1.00
	Electric resistance welding	1.00
	Furnace Butt welded: continuous weld	0.60
ASTM A 106	Seamless	1.00
ASTM A 134	Electric Fusion Arc Welded	0.8
ASTM A 135	Electric resistance welded	1.00
ASTM A	Electric Fusion welded	0.8

139			
ASTM 211	A	Spiral welded steel pipe	0.8
ASTM 333	A	Seamless Electric resistance welding	1.00 1.00
ASTM 381	A	Double submerged arc welding	1.00
ASTM 671	A	Electric fusion welded Classes 13,23,33,43,53 Classes 12,22,32,42,52	0.80 1.00
ASTM 672	A	Electric fusion welded Classes 13,23,33,43,53 Classes 12,22,32,42,52	0.80 1.00
API 5L		Seamless Electric resistance welding Electric flash welded Submerged arc welded Furnace butt welded	1.00 1.00 1.00 1.00 0.60

Through the above process the optimum material and wall thickness combination is identified.

For this pipeline

$P=70.1 \text{ kg/cm}^2 \text{ g}$,

$D= 24'' (610\text{mm})$,

$E=1$,

$S= 70000 \text{ psia (grade-X-70) or } 4921.612 \text{ kg /cm}^2$,

So if we calculate thickness for class 1 i.e. $F = .72$

$$t = (70.1 * 610 / 2 * 1 * 1 * 4921.612 * .72)$$

$$t = 7.1 \text{ mm}$$

For crossings having open cut, F = 0.6 then

$$t = (70.1 * 610 / 2 * 1 * 1 * 4921.612 * 0.6)$$

$$t = 7.9 \text{ mm}$$

For crossings having Horizontal Directional Drilling (HDD) : F = 0.5

$$t = (70.1 * 610 / 2 * 1 * 1 * 4921.612 * 0.5)$$

$$t = 11.1 \text{ mm (seismic area)}$$

The wall thickness selected for the proposed pipelines are summarized in Table: 3

Table: 3 Wall Thickness Summary.

Pipeline size (inch)	Area	Design factor	Line pipe material API 5L	Calculated wall thickness (mm)	Selected thickness (mm)
24"	In all places	0.72	Gr.X- 70	7.03	7.1
24"	Open cut	0.6	Gr.X- 70	7.2	7.9
24"	HDD	0.5	Gr.X- 70	11.1	11.9

3.3 Horizontal Directional Drilling [1, 3]:

There are two stages to directional drilling; the first involves drilling a small diameter pilot hole along a designated path, while the second one involves enlarging the hole to accommodate the pipeline. A steering bias is created by the asymmetry of the leading edge. If a change in direction is required; the drill string is rolled so that the direction of bias is the same as the desired change in direction. Drilling progress is normally achieved by hydraulic cutting action with a jet nozzle. Mechanical cutting action, when required, is provided by a down hole positive displacement mud motor.

The actual path of the pilot hole is monitored during drilling by taking periodic readings of the inclination and azimuth of the leading edge. These readings, along with measurements of the distance drilled since the last survey, are, used to calculate the horizontal and vertical coordinates along the pilot hole, relative to the initial entry point on the surface.

The pilot hole is enlarged using a reaming process, which can either form part of the pullback process or be completed prior to it. Ordinarily the reaming tool is attached to the drill pipe at the exit point. The drill pipe is then drawn toward the drilling rig as the reamers rotate, thus enlarging the pilot hole. Sections of drill pipe are continuously added as progress is made, to ensure that there is always a string of pipe in the hole. The reaming tools consist of a circular set of cutters and drilling fluid jets. The pressurized drilling fluid serves three purposes: to cool the cutting tools, support the reamed hole, and lubricate the trailing drill pipe. In soft soils with small-diameter lines, pre-reaming is unnecessary and the final installation phase is undertaken when the pilot hole has been completed. In this circumstance the reaming assembly is attached to the actual pipeline pull section and sections of pipe are added as the reamer progresses towards the drilling rig. In order to minimize the torsion acting on the pipeline a swivel is used to attach the pull section to the leading reamer.

3.4 VALVES [Annexure]:

The entire length of the pipeline is divided into several sections by installing valves at certain intervals of length. This allows isolation of a section of pipeline in case of any emergency of a section of pipeline in case of any emergency such as bursting or leakage etc.

Application of various types of valves shall be as follows:

Valve type	Typical application
Ball	On/off, isolation (on main line)
Plug	On/off, isolation (in the terminals)
Check	Uni-directional flow

All pipeline valves shall comply with the requirements of API 6D/ relevant PMS. Ball valves shall have primary metal-seated design. In order to minimize potential leak sources, valves used in mainline shall be with butt-weld ends. Valve installed within the terminal to isolate the mainline/ pipeline shall also be provided with butt-welding ends. However terminal valves shall be flanged ends. Flanges may be used where frequent access or removal of equipment is required.

Wherever underground valves are provided, valves shall be provided with a stem extension in such a way that the centerline of the rim of the hand wheel on a horizontal shaft or center of power actuator is approximately 1.0 m above the finished ground level. Minimum size of any tapping from the underground pipeline shall be 2" NB and shall be provided with an isolation ball valve located at a minimum distance from the pipeline.

3.4.1 Required Spacing of Sectionalising Valves:

(a) When determining the sectionalizing valve spacing, primary consideration will be given to locations that provide continuous accessibility to the valves.

(b) The spacing between valves on a new transmission line should not exceed 30 miles in general location. However valves are required to be placed on either side of the water bodies crossings.

Valves on distribution mains, shall be spaced as follows:

(a) High pressure systems:

Valves installed in accessible location to reduce the time to shut down a section during emergency and due consideration given to size of mains, operating pressure, local physical conditions as well as number and type of human life's affected by the shutdown

3.4.2 Location of Valves (Transmission Valves)

(a) Sectionalizing block valves should be accessible and protected from damage and tempering.

(b) Sectionalizing valves should be installed above ground, in a vault or buried.

(c) Blow down valves should be provided such that each section of the pipeline between main line valves can be blown down.

3.5 PIPING [3]:

This section describes the design requirements of piping applicable for dispatch station, intermediate pigging stations, sectionalizing valve stations and receiving station. All piping and equipment shall be designed as per ASME B 31.4. All piping materials shall be as per Piping Material Specification (PMS). Utility piping to be provided shall be designed in accordance with the provisions of ASME B 31.3. Design shall provide consideration for all loadings like weight, temperature etc., significantly affecting the pipe material stresses in addition to fluid pressure.

3.5.1 Piping Flexibility/Stress Analysis:

All piping shall be designed for thermal expansion under start up, operating and shut down conditions without over stressing the piping, valves or equipment. Provisions for expansion shall normally be made with bends and offsets.

All piping shall be adequately supported, guided or anchored so as to prevent undue vibration, deflection or loads on connected equipments. Equipments/ valves requiring periodical maintenance shall be supported in such a way that the valves and equipment can be removed with minimum temporary pipe supports.

3.5.2 Piping layout

Piping will be located above ground wherever possible within the terminals.

- Piping shall be designed considering skin temperature of piping material under empty conditions as 65°C or design temperature of pipeline whichever is higher.
- Piping stress analysis shall be carried out to determine allowable pipe movement and support requirements wherever felt necessary.
- Buried piping inside the terminal area will have a minimum depth of cover of 1.2 m.
- Where buried pipes come out of the ground, the underground coating on the pipe will continue for a distance of 500 mm above ground.
- Platforms, crossovers shall be provided for ease of operation and maintenance.
- Platform for filters shall be provided for maintenance/ operational access.
- Painting above ground piping and structures shall be as per specifications enclosed in the Bid package. Painting suitability shall be as under:

-Coastal and Marine environment for Vadinar terminal.

-Normal industrial environment for all other stations and terminals.

3.6 Scraper Stations [1, 3]:

Scraper traps shall be provided at the dispatch terminal, intermediate pigging stations. The scraper traps shall be uni-directional capable of handling intelligent pigs and other cleaning pigs. The launching and receiving barrels shall be designed in accordance with the requirements of ASME B 31.4 and its end closure shall be designed and

fabricated according to ASME Section VIII, Div.1. Adequate arrangements for launching, retraction, handling and lifting of cleaning and instrumented pigs shall be provided at the scraper stations. Traps shall be accessible by walkway/road for movement of equipment, pigs etc. These stations shall be provided with access road from the nearest metalled road.

The diameter of barrel of the launcher cum receiver shall be three nominal sizes larger than the pipeline nominal size. Centerline elevation of scraper trap shall be at suitable height from grade level. Suitable arrangements shall be provided for handling & lifting of pigs. The piping system at the terminals and intermediate stations shall be designed to have sufficient flexibility to prevent pressure and thermal expansion or contraction from causing excessive stresses on the connected equipment. The piping shall be designed/fabricated as defined in clause 8.3.

3.7 Welding [Annexure]:

Welding shall be carried out in accordance with API 1104, specification for welding and welding charts. Butt welds shall be radio graphed / automatic UT for automatic welding, as applicable for all pipelines.

For gas service all butt welds for process piping shall be 100% radiographed and for utility piping NDT requirements shall be as per specification

3.8 Crossings [1, 2, 3]:

3.8.1 Water Crossings

All water crossing shall be installed by open cut. Wherever there is an evidence of bank erosion, the banks shall be protected by using gravel and boulders filled embankment mattresses of galvanized iron wire to be laid over the backfilled, compacted and graded banks.

3.8.2 Road Crossing

Road crossings shall comply with the requirements of API 1102 and the requirements of the concerned road authorities. Unless otherwise required by concerned Authorities, casing pipe shall not be used. However at national highway road crossings pipeline

shall be provided with casing pipe, which shall extend min. 600 mm beyond Road ROW on either side. The casing pipe shall be installed by trench less method like ramming/ boring/ jacking/ HDD /Micro Tunneling. Provision of casing at locations other than national highways shall be decided based on type of road crossing and as per requirements of local authorities if necessary. The casing pipe shall be three nominal pipe sizes larger than carrier pipe. The crossing angle shall be as close to 90° as possible. Casing insulators and end seals shall be provided to ensure electrical isolation of carrier pipe and casing pipe.

3.8.3 Rail Crossing

Pipeline at rail crossings shall be provided with casing pipe. The casing pipe shall be three nominal pipe sizes larger than carrier pipe (unless advised otherwise by concerned authorities) and shall be installed by boring/ jacking/ HDD/ ramming. The rail crossing shall comply with the requirements of API 1102 and Indian Railway Authorities. The crossing angle shall be as close to 90° as possible. It should be noted that the extent of casing pipe generally specified by Railways is 14.0 m beyond centerline of the outermost tracks on either side or 0.6 meter beyond the ROU limits of Railways on either side, whichever is more. Carrier pipe shall be electrically insulated from the casing pipe and casing ends shall be sealed using durable, electrically non-conducting materials. The crossing drawing shall be subject to approval of concerned Railway Authorities prior to implementation.

3.8.4 Existing Pipeline Crossing

The minimum clearance between the lines shall be 300 mm unless specified otherwise.

3.9 External/Internal Corrosion Coating [1, 2, 3]:

Pipeline to be installed below ground shall be protected against external corrosion by a combination of high integrity externally applied coatings and permanent impressed cathodic protection system. Externally applied coating shall be three layer side extruded polyethylene coating. In addition, pipeline shall be provided with internal roughness of 45-micron and corrosion allowance of 1mm.

All above ground piping and structures shall be painted to prevent atmospheric corrosion. Painting of above ground piping and structures shall be as per specifications. Painting shall be suitable for normal corrosive environment/corrosive environment, as applicable.

3.10 Hydrostatic Testing [Annexure]:

Hydrostatic test is essential for the pipeline to prove that the pipe has the strength required to meet the design conditions, and to verify that the pipe is leak free. It is a major operation and should be carefully planned. Estimating the hydrostatic test pressure before the construction work have finished is done by the following method [2, 3, 4].

1. We draw the ground profile of the pipeline, marking on the profile the rivers wherever existing.
2. Then we examine the elevation gradient, the gradient along with the location of the water source and the pipe design data, it will be used to determine the length and the number of test sections.
3. Where the pipe traverses hilly terrain, the elevation gradient must be carefully studied in selecting the pipeline test segments.

In this particular pipeline the range of allowable percentages is 90% of SMYS. And the hydrostatic test pressure is 1.25 times the design pressure

The design pressure = 70.1 kg/cm^2

D= 610mm

T=7.1, 7.9, 11.9mm according to the classes

SMYS= 70000

Thus $P_H = 1.25 * 70.1 = 87.63 \text{ kg/cm}^2$

CHAPTER: 4

PROCESS DESIGN BASIS

4.1 Battery Limits [6]:

Battery limits is the name given for dispatch and receiving terminals. Bharat Oman Refineries Limited (BORL) is setting up a grass root refinery complex at Bina, M.P for which following facilities are visualized:

- (a) Single Point Mooring (SPM) of CALM type near Vadinar, Gujarat and associated offshore/onshore pipelines up to Crude Oil Terminal (COT).
- (b) Onshore Crude Oil Terminal (COT).
- (c) Approx. 935 km Vadinar-Bina pipeline (VBPL) from COT to Refinery.

This document covers the design basis for approximately 935 km long Vadinar-Bina pipeline from COT outlet header at Vadinar to inlet header of crude oil tanks in the refinery at Bina.

Battery Limit Conditions

1. At Vadinar

Inlet flow, MMTPA (m^3/hr)	:	6.0 (862)
Battery Limit Pressure, kg/cm^2 g	:	42
Battery Limit Temp, $^{\circ}C$ (max/min)	:	35/10

2. At Bina refinery receipt terminals

Inlet flow, MMTPA (m^3/hr)	:	6.0 (862)
Battery Limit Pressure, kg/cm^2 g	:	5
Battery Limit Temp, $^{\circ}C$ (max/min)	:	35/10

4.2 Pipeline Parameters [6]:

Trunk line (Vadinar to Bina):

i) Pipeline OD	:	24"
		(API 5L Gr X 70)
ii) Pipeline length, km	:	935

iii) Pipe thickness, mm

for various considerations	:	7.1/7.9/11.9
v) Design temperature above ground/buried, °C	:	35 °C/10° C
vi) Pipe internal roughness	:	45 microns
vii) Pipe corrosion allowance	:	1.0 mm
viii) Sub-soil temperature, °C	:	25
ix) Pipeline laying	:	Buried
x) Ground profile	:	Elevation is considered.
xi) Pipeline external protection:	:	Suitable coating and impressed current cathodic protection shall be provided.
xii) Pigging facilities	:	suitable for intelligent pigging shall be provided as required.
xiii) Operating hours	:	8000/Annum
xv) Design Life	:	30 Years

4.3 Elevations [6]:

COT tank bottom elevation, m (above MSL)	:	10 (max)
Height (maximum) of COT tanks , m	:	20
Refinery tank bottom elevation, m (above MSL)	:	400-420
Height (maximum) of refinery tanks, m	:	20

4.4 Utilities [6]:

BORL shall make following utilities required at consumer terminals available.

- For effective maintenance of pipeline, pig launching / receiving facilities (for intelligent pigs) will be provided at the crude despatch, crude receipt in the refinery and intermediate locations along the pipeline.

-The arrangements for all the utilities required for the total system comprising of booster and mainline pump station at COT, intermediate pump stations, sectionalising valve stations and intermediate pigging stations are within the scope of this project.

- Tapping and distribution for fire water and drinking water is outside the scope of this part of the project.

4.5 Instrumentation and Control [6]:

Adequate instrumentation and control system shall be provided for safe and efficient operation. Pipeline is envisaged to be monitored and controlled from SCADA (Supervisory Control & Data Acquisition) monitoring & control station (SMCS), which will be located at the crude oil terminal at Vadinar. The SMCS shall be interlinked through pipeline communication system with Remote Terminal Units (RTU) located at each pumping, pigging, SV stations, receipt terminal and other locations along the pipeline.

4.5.1 Method of communication:

Optical fiber cable (data, voice & video communication). The telecommunication system shall be based on STM4 (minimum) with 12-fibre optical fibre cable. Back-up data & voice communication through lease line /VSAT shall be provided.

4.5.2 Electric power

Electric power shall be made available at all the stations through state electricity board grids. Emergency power generator shall meet emergency power requirement. For details, refer the relevant electrical design basis.

4.6 Metering [6]:

Metering facilities shall be provided at crude despatch facility in the crude oil terminal (COT) at Vadinar, at intermediate pumping stations and at crude receipt terminal in the refinery. Metering shall be through Turbine meters. One standby meter run shall be provided. Flow meters shall be provided at each metering point.

Density cum viscosity meter shall be provided at despatch and receipt terminals for density and viscosity measurement of crude oil and leak detection purpose.

Pressure and temperature monitoring shall be provided at each pumping, intermediate pigging and sectionalising valve (SV) stations.

4.7 Temperatures [6]:

4.7.1	Average sub-soil temperature, deg C	:	20
4.7.2	Ambient Temperature (max/min), deg C	:	42.9 / 0.7
4.7.3	Pumping Temperature (max/min), deg C	:	35 / 10
4.7.4	Design temperature		
	Buried, deg C	:	45
	Above ground, deg C	:	65

4.8 Pumps [6]:

4.8.1 Sparing and Operation Philosophy for Pumps:

- Two (2) working & one (1) stand by for booster and mainline crude oil pumps.
- One (1) working & one (1) stand by for corrosion inhibitors injection pumps.
- One (1) working & zero (0) stand by for sump pumps.
- One (2) working & zero (0) stand by for slop transfer pumps.

4.8.2 Choice Of Drives For Pumps:

At COT/ Intermediate pumping stations: All pumps will be electrically driven.
Booster pumps at COT will be having fixed speed drive.

Mainline crude oil pumps at COT as well as at intermediate pump stations will have variable speed drive.

4.9 Crude Characteristics [6]:

Table: 4 Properties of Crude Oil

Property	Design Case	Check Case	
	Case-I (ARAB MIX)	Case-II (OMAN)	Case-III (KUWAIT)
Specific Gravity (15.56/15.56 °C)	0.8722	0.8503	0.8739
Viscosity, cst	1.5 @ 129 deg.C 6.0 @ 30 deg.C	16.7 @ 20 deg C 8.5 @ 40 deg C	2.7 @ 100 deg.C 2.8 10 @37.8deg.C
Pour Point, deg C	< (-)5	(-) 42	(-) 21
RVP, kg/cm2a	0.3-0.7	0.3-0.7	0.3-0.7
Sulphur content, wt. %	2.42	0.95	2.6
Water content, vol %	2	2	2

4. 10. Sectionalizing Valve Stations [Annexure]:

Sectionalizing valve station shall be provided along pipeline route for isolating sections of pipeline as per ASME B 31.4 for:

- Limiting the hazard and damage from accidental discharge from pipeline system.
- Facilitating maintenance of pipeline system and

- Complying with the requirements of applicable codes.

The location of sectionalising valves shall be as per the requirements of applicable codes taking consideration of terrain features, requirement of safety and operation etc. Sectionalising valve on the main pipeline shall be ball valves of full bore type, to allow smooth passage of pigs.

All valves installed at Intermediate facilities, block valve stations, scraper stations and pipeline sectionalising valve stations shall be gas actuated/ hand operated and with butt-welded ends. Sectionalising and Station block valves shall be installed buried and provided with a stem extension in such a way that the centerline of rim of the hand wheel on a horizontal shaft or center of actuator is at approximately 1.0 m above the finished ground level. Valve surface shall be provided with corrosion protection coating. Valve body vent and drain lines shall be extended and terminated above ground.

The valve stations are normally located at a readily accessible location such as near road and shall be provided with an access road from the nearest all weather metalled road. The facilities within valve station shall be secured by a chain link fence enclosure with gate. The location of valve station shall be clear of overhead power lines.

The provisions of remote operated feature shall be as per the operation and control philosophy to be adopted for the project. At locations, where valve stations are combined with CP/Repeater stations, the safe distance and statutory clearance as per standard shall be followed.

CHAPTER: 5

SIMULATION

5.1 Steady State Vs Transient Simulation [5]:

Transient Liquid Net (TLNET) performs two types of simulation runs. A steady state run calculates time invariant pressure, temperature and flow profiles throughout the pipeline system, which results from specified boundary conditions and equipment set points entered by the user. In other words, the steady state run calculates the hydraulic state of a pipeline system operating at equilibrium. This type of simulation may be done just to obtain steady state data or to provide the initial condition (i.e. initial state/initial profiles) from which to start a transient run.

A transient run models the dynamic response of the pipeline system to changes in one or more system variables such as source/delivery rates or equipment set points. Transient calculations are more complex and require more computer time than steady state calculations. Useful results can be obtained from a transient simulation only if changes occur in or more of the parameters governing the system. Thus, the transient portion of the program should be run only if one or more ramp schedule with time-varying quantities is entered or if a batch tracking simulation is needed.

Naturally, then first time a model is run with a new network, there will have been no previous simulation. Thus, at least one steady state simulation will have to be run to calculate initial profiles. However, each time the same data are reused for subsequent transient runs with or without a limited set of changes), the steady state run can be bypassed by using the initial state or final state of the previous transient simulation. If this is done, the user may only change constraints, set points, schedules, or report/trend options. The user cannot strip the steady state run if changes are made to then physical pipeline configuration.

5.2 Choosing The Simulation Timetable [7]:

The simulation can be divided into any number of predefined ramp intervals for calculation and reporting purposes. The user should determine the length of the transient simulation. This depends on the phenomenon being simulated.

Example: to simulate a daily delivery cycle, simulation length would be 24hours (1440mts/86400seconds- depend upon time unit).

If a system upset were being modeled, the simulation length would be the amount of time the user thinks it might take for the transient conditions to propagate through the pipeline network system.

The simulation period is divided into ramp intervals, which should correspond to the beginnings and endings of all changes, which occur during the transient simulation. Each interval is used to set up a time increment for ramping. Changes in flow, pressure or other set point/constraints in the system. The value being changed is ramped linearly over the specified time interval, beginning with the value specified or calculated) for the present interval.

5.3 TLNET Applications [5]:

It is used for two general types of studies, they are as follows:

Simulating normal operation of various pipeline configurations to determine the most efficient design or mode of operation. Simulating transient conditions caused by events such as leaks or equipment failures to predetermine the most effective corrective action.

To study an existing system, for example the base case would logically be a simulation of the system under normal. Steady state operating conditions followed by a simulation of any normally occurring time varying phenomena. Subsequent runs would simulate changes in pipeline operation due too design modifications or dynamic condition, depending on which is being analysed. By comparing the results of these

test runs to the base case, the user can determine the most effective design change (if required) or modification of operational procedures.

From this (TLNET), we can able to determine maximum pipeline throughput in proposed/existing systems, simulate pipeline surge, simulate pipeline leak and study transient response, predict environmental impact of pipeline leakage, analyse pipeline deliverability, and reduce operating cost.

5.3.1 To determine maximum pipeline throughput:

The increase in flow that is possible without violating the minimum line pressure at a delivery point.

5.3.2 To simulate pipeline surge:

Leaks, valve closure, pump startup/shutdown and other factors can cause pressure surge in the pipeline, which could be potentially damaging. We can design to simulate upset conditions and determine if pressure surge will exceed design criteria anywhere within the network.

5.3.3 To Analyse pipeline deliverability:

The deliverability of a pipeline system operating during peak season can be analysed to determine whether the system can meet increasing future demands or whether additional equipment is needed. Strategies such as production to and from tankage and scheduling (startup/shutdown) of key pump units can be investigated.

5.3.4 To reduce operating costs:

Pumps can be optimally scheduled so as to minimize power costs. In addition, individual pumps or pump stations can be accurately modeled by input of manufacturer provided pump head and efficiency curves. Thus fuel/electrical use associated with a given operating scenario can be evaluated and based on case studies an optimum mode of operation can be selected.

Before simulating the operation of a pipeline network, many decisions must be made:

- How will the network be configured?
- What factors should be analysed?
- What time period should the simulation cover?
- Which system variables are to be ramped and on what kind of schedule?
- A schematic should be drawn and each of the elements to be modeled should be assigned identification?

The user should also determine the constraint for the pipeline system to be modeled and whether a steady state/transient run is required. The components must be defined before drawing the schematic. A pipeline system is viewed as a network of interconnecting components including legs, nodes, equipment and external regulators which are joined together in a specific configuration. Components are defined as follows:

5.4 Legs [5]:

Leg is any segment of pipe that has uniform characteristics along its entire length. These characteristics include inside diameter, wall thickness, and absolute roughness and for temperature tracking purposes only, ambient temperature and overall heat transfer coefficient. A pipeline is broken into leg segments at any point where any of these parameters change. A leg is always connected to nodes at both the head (upstream) and tail (downstream) ends. Leg is further divided into knots (as smaller intervals). TLNET calculates pressure, density and velocity at every knot.

5.5 Transient Analysis Has Been Cited For Application Of [3]:

Pipeline construction economics (use of surge control system vs. higher wall thickness pipe). Pipeline pumps station design and operation.

-Station control valve design for pressure overrides logic to protect pipeline from over pressurization.

-Effect of rapid valve closures.

- Effect of rapid flow (supply/demand) fluctuations.
- Pressure surge relief system design.
- Lines break control.
- Waxy crude transportation.

5.6 Steps Involved in Simulation [5]:

The following equations are involved in TLNET simulator.

5.6.1 Hydraulic Equations:

Equations needed are mass, momentum and energy balance equations.

5.6.2 Friction Factor:

From the calculation of Reynolds Number (NRe), the flow can be differentiated as laminar or turbulent.

5.6.3 Drag Reduction:

In general, equations involved are Burger Correlation or Conoco correlation.

5.6.4 Equipment and External Regulator Equations:

- Leak simulation external regulator.
- Resistance equipment.
- Block valves.
- Pumps details (head, performance curve, break power and shaft power).

5.6.5 Physical Properties of Liquid:

Properties such as density, bulk modulus, coefficient of thermal expansion, heat capacity and viscosity.

By Cole Brook white Equation [4]:

$$Q=C_4 S_q \text{ Root of } (1/f). D^{2.5} [(p_1-p_2-\Delta PE)/L.G]^{0.5} (\text{bpd})$$

Pressure Drop [4]:

$$\Delta P = p_1 - p_2 - \Delta PE$$
$$= (f \cdot L \cdot G \cdot Q^2) / (C_4^2 \cdot D^5)$$

where,

Q= flow of liquid (bpd).

$C_4 = 19.8072E -6$

D=inside dia (inches).

f=friction factor.

p_1 = upstream pressure (psia).

p_2 = downstream pressure (psia).

ΔPE = elevation changes (psia).

L= pipeline length (miles).

G= specific gravity of liquid.

23: KNOT 4.0
24:
25:

26: *CONTROL
27:
28: SCREEN
29: PROFILE
30: ICNS = 50
31: ITMX = 100
32:
33:

34:
35: *CONFIG
36:
37: XREG=VADINAR AT=N01 SUPPLY FLMX=862 MODE=FLMX
38: PUMP=PUMPVAD UP=N01 DN=N02 PUPMN=2 MODE = PUPMN
39: PIPE=L1 UP=N02 DN=N03 L=182.731 ID=23.44
40:
41:; BLKV=BLKVIP1 UP=N03 DN=N03A CV=110000 VSIZE=24
PCTOP=100
42: PIPE=L2 UP=N03 DN=N05 L=168.119 ID=23.44
43:
44: PUMP=PUMPIP2 UP=N05 DN=N06 PUPMN=5.0 MODE = PUPMN

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 2

----- COLUMN NUMBER -----
CARD 1 2 3 4 5 6 7
NO.
12345678901234567890123456789012345678901234567890890456789012

45: PIPE=L3 UP=N06 DN=N07 L=125.852 ID=23.44
46:
47:; PUMP=PUMPIP3 UP=N07 DN=N08 PUPMN=5.0 MODE = PUPMN
48: PIPE=L4 UP=N07 DN=N09 L=79.347 ID=23.44
49:
50: PUMP=PUMPIP4 UP=N09 DN=N10 PUPMN=5.0 MODE = PUPMN
51: PIPE=L5 UP=N10 DN=N11 L=198.029 ID=23.44
52:
53:; PUMP=PUMPIP5 UP=N11 DN=N12 PUPMN=5.0 MODE = PUPMN
54: PIPE=L6 UP=N11 DN=N13 L=180.922 ID=23.44

55: BLKV=BLKVST UP=N13 DN=N13A CV=53500 VSIZE=24
 PCTOP=100
 56: PIPE=L7 UP=N13A DN=N13B L=0.05 ID=23.0
 57: RESI=CVBINA UP=N13B DN=N13C F=1 L=790 D=24
 58: XREG=SRV AT=N13C DELIV PMIN=12.0 MODE=PMIN CHECK
 59: RESI=METERBINA UP=N13C DN=N13D F=1 L=404 D=24
 60: PIPE=L8 UP=N13D DN=N13E L=0.95 ID=23.0
 61: BLKV=BLKVCOT UP=N13E DN=N13F CV=53500 VSIZE=24
 PCTOP=100
 62: XREG=BINA AT=N13F DELIV PMIN=2.00 MODE=PMIN CHECK
 63:
 64:

65:*USRLINE

66:
 67: USERLINE=MAIN HEADPOST= 0.0
 68:
 69: HEAD XREG = VADINAR
 70: COMP NODE = N01
 71: COMP EQUIP = PUMPVAD
 72: COMP NODE = N02
 73: COMP LEG = L1
 74: COMP NODE = N03
 75:; COMP EQUIP = BLKVIP1
 76:; COMP NODE = N03A
 77: COMP LEG = L2
 78: COMP NODE = N05
 79: COMP EQUIP = PUMPIP2
 80: COMP NODE = N06
 81: COMP LEG = L3
 82: COMP NODE = N07
 83:; COMP EQUIP = PUMPIP3
 84:; COMP NODE = N08
 85: COMP LEG = L4
 86: COMP NODE = N09
 87: COMP EQUIP = PUMPIP4
 88: COMP NODE = N10
 89: COMP LEG = L5
 90: COMP NODE = N11
 91:; COMP EQUIP = PUMPIP5
 92:; COMP NODE = N12
 93: COMP LEG = L6
 94: COMP NODE = N13
 95: COMP EQUIP = BLKVST

96: COMP NODE = N13A
97: COMP LEG = L7

----- COLUMN NUMBER -----
CARD 1 2 3 4 5 6 7
NO.
12345678901234567890123456789012345678901234567890890456789012

98: COMP NODE = N13B
99: COMP EQUIP = CVBINA
100: COMP NODE = N13C
101: COMP EQUIP = METERBINA
102: COMP NODE = N13D
103: COMP LEG = L8
104: COMP NODE = N13E
105: COMP EQUIP = BLKVCOT
106: COMP NODE = N13F
107: TAIL XREG = BINA

108:
109:
110:LINEPOST = 0.00 LINEELEV = 10.0
111:LINEPOST = 100.0 LINEELEV = 60.0
112:LINEPOST = 125.0 LINEELEV = 130.0
113:LINEPOST = 150.0 LINEELEV = 100.0
114:LINEPOST = 160.0 LINEELEV = 160.0
115:LINEPOST = 180.0 LINEELEV = 160.0
116:LINEPOST = 250.0 LINEELEV = 10.0
117:LINEPOST = 320.0 LINEELEV = 10.0
118:LINEPOST = 385.0 LINEELEV = 30.0
119:LINEPOST = 400.0 LINEELEV = 90.0
120:LINEPOST = 405.0 LINEELEV = 70.0
121:LINEPOST = 460.0 LINEELEV = 280.0
122:LINEPOST = 475.0 LINEELEV = 410.0
123:LINEPOST = 490.0 LINEELEV = 290.0
124:LINEPOST = 500.0 LINEELEV = 330.0
125:LINEPOST = 510.0 LINEELEV = 370.0
126:LINEPOST = 515.0 LINEELEV = 290.0
127:LINEPOST = 525.0 LINEELEV = 370.0
128:LINEPOST = 530.0 LINEELEV = 310.0
129:LINEPOST = 550.0 LINEELEV = 410.0
130:LINEPOST = 570.0 LINEELEV = 430.0
131:LINEPOST = 580.0 LINEELEV = 390.0

NUMBER OF TURBINE TYPES: 0

TLNET VERSION 5.1

A PROPRIETARY PRODUCT OF SS-I

PAGE 7

TLNET INITIAL STATE OUTPUT OPTIONS REPORT

REPORT TYPES:

- 0 = NO REPORT
- 1 = SUMMARY REPORT
- 2 = DETAIL REPORT

*** LEG REPORT OPTIONS

LEG HYDRAULIC REPORT: 2

REPORTING ALL LEGS

*** PUMP REPORT OPTIONS

PUMP HYDRAULIC REPORT: 2

REPORTING ALL PUMPS

*** REGULATOR REPORT OPTIONS

REGULATOR HYDRAULIC REPORT: 1

REPORTING ALL REGULATORS

*** BLOCK VALVE REPORT OPTIONS

BLOCK VALVE HYDRAULIC REPORT: 1

REPORTING ALL BLOCK VALVES

*** CHECK VALVE REPORT OPTIONS

CHECK VALVE HYDRAULIC REPORT: 1

REPORTING ALL CHECK VALVES

*** RESISTANCE REPORT OPTIONS

RESISTANCE HYDRAULIC REPORT: 1

REPORTING ALL RESISTANCES

*** EXTERNAL REGULATOR REPORT OPTIONS

EXTERNAL REGULATOR HYDRAULIC REPORT: 2

REPORTING ALL EXTERNAL REGULATORS

*** TANKAGE REPORT OPTIONS

TANKAGE HYDRAULIC REPORT: 1

REPORTING ALL TANKS

*** BATCH REPORT OPTIONS

BATCH REPORT: 0

*** NODE MASS BALANCE REPORT OPTIONS

NODE MASS BALANCE REPORT: 0

TREND REPORT

The following External Regulators have been selected:
VADINAR SRV BINA

With the following values:

Pressure Temperature
Flow Mode
Maximum Flow Setpoint Minimum Pressure Setpoint
Accumulated Volume

Total Number of Trended data values for this entry is 18

The following Nodes have been selected:

N01 N02 N03 N05 N06 N07 N09 N10 N11
N13 N13A N13B N13C N13D N13E N13F

With the following values:

Pressure Temperature
Density Flux

Total Number of Trended data values for this entry is 64

MAX, TREND EVERY TIME STEP

TRANSIENT SIMULATION SCENARIO REPORT

*** AUTOMATIC TIME STEP OPTIONS

MINIMUM TIME STEP: (MINS) 0.017

MAXIMUM TIME STEP: (MINS) 166.667
 ACCURACY LEVEL : 5.00

*** TRANSIENT SIMULATION TIMETABLE

RAMP NO.	TIME (MINS)	
	FROM	TO
1	0.000	2.000
2	2.000	4.000
3	4.000	4.500
4	4.500	6.500
5	6.500	15.000

*** EQUIPMENT SETPOINT/CONSTRAINT RAMP SCHEDULE

EQUIPMENT: BLKVST

CURRENT RAMPED SETPOINT/CONSTRAINT TYPES

SETPT/ CNSTRT NO	DESCRIPTION
1	PERCENT OPEN SETPOINT

SCHEDULE FOR PERCENT OPEN SETPOINT

RAMP NO.	TIME (MINS)		SETPOINT/CONSTRAINT VALUE
	FROM	TO	
		0.000	100.000
1	0.000	0.000	100.000
2	0.000	2.000	100.000
3	2.000	4.500	100.000
4	4.500	6.500	0.000
5	6.500	15.000	0.000

EQUIPMENT: BLKVCOT

CURRENT RAMPED SETPOINT/CONSTRAINT TYPES

SETPT/
CNSTRT
NO DESCRIPTION

1 PERCENT OPEN SETPOINT

SCHEDULE FOR PERCENT OPEN SETPOINT

RAMP NO.	TIME (MINS)		SETPOINT/CONSTRAINT VALUE
	FROM	TO	
		0.000	100.000
1	0.000	0.000	100.000
2	0.000	2.000	100.000
3	2.000	4.000	0.000
4	4.000	15.000	0.000

*** EXTERNAL REGULATOR SETPOINT/CONSTRAINT RAMP SCHEDULE

*** INLET FLUID CONDITIONS RAMP SCHEDULE

TLNET VERSION 5.1

A PROPRIETARY PRODUCT OF SS-I

PAGE 10

LIQUID TYPES REPORT

NUMBER OF LIQUID TYPES: 1

CURRENT LIQUID PROPERTIES FOR TYPE: CRUDE

*** BULK MODULUS DATA

BULK MODULUS

POINT NO	TEMP (DEG C)	PRESSURE (KG/CM2)	GRAVITY (DG API)	MEASURED (KG/CM2)	CURVE FIT (KG/CM2)	REL ERR (%)
1	5.0	1.0	30.00	16091.	16089.	0.01
2	5.0	50.5	30.00	16091.	16089.	0.01
3	5.0	100.0	30.00	16091.	16089.	0.01
4	15.0	1.0	30.00	15198.	15198.	0.00
5	15.0	50.5	30.00	15198.	15198.	0.00
6	15.0	100.0	30.00	15198.	15198.	0.00
7	25.0	1.0	30.00	14355.	14358.	0.02
8	25.0	50.5	30.00	14355.	14358.	0.02
9	25.0	100.0	30.00	14355.	14358.	0.02
10	5.0	1.0	35.00	14958.	14956.	0.02
11	5.0	50.5	35.00	14958.	14956.	0.02
12	5.0	100.0	35.00	14958.	14956.	0.02
13	15.0	1.0	35.00	14080.	14080.	0.00
14	15.0	50.5	35.00	14080.	14080.	0.00
15	15.0	100.0	35.00	14080.	14080.	0.00
16	25.0	1.0	35.00	13254.	13255.	0.01
17	25.0	50.5	35.00	13254.	13255.	0.01
18	25.0	100.0	35.00	13254.	13255.	0.01

*** COEFFICIENT OF THERMAL EXPANSION DATA

THERM EXPAN COEFF						
POINT NO	TEMP (DEG C)	PRESSURE (KG/CM2)	GRAVITY (DG API)	MEASURED 1/(DEG C)	CURVE FIT 1/(DEG C)	REL ERR (%)
1	5.0	1.0	30.00	0.7887E-03	0.7882E-03	0.06
2	5.0	50.5	30.00	0.7887E-03	0.7882E-03	0.06
3	5.0	100.0	30.00	0.7887E-03	0.7882E-03	0.06
4	15.0	1.0	30.00	0.7989E-03	0.7989E-03	0.00
5	15.0	50.5	30.00	0.7989E-03	0.7989E-03	0.00
6	15.0	100.0	30.00	0.7989E-03	0.7989E-03	0.00
7	25.0	1.0	30.00	0.8091E-03	0.8096E-03	0.05
8	25.0	50.5	30.00	0.8091E-03	0.8096E-03	0.05
9	25.0	100.0	30.00	0.8091E-03	0.8096E-03	0.05
10	5.0	1.0	35.00	0.8203E-03	0.8207E-03	0.05
11	5.0	50.5	35.00	0.8203E-03	0.8207E-03	0.05
12	5.0	100.0	35.00	0.8203E-03	0.8207E-03	0.05
13	15.0	1.0	35.00	0.8314E-03	0.8314E-03	0.00
14	15.0	50.5	35.00	0.8314E-03	0.8314E-03	0.00
15	15.0	100.0	35.00	0.8314E-03	0.8314E-03	0.00

16	25.0	1.0	35.00	0.8425E-03	0.8421E-03	0.05
17	25.0	50.5	35.00	0.8425E-03	0.8421E-03	0.05
18	25.0	100.0	35.00	0.8425E-03	0.8421E-03	0.05

*** HEAT CAPACITY DATA

HEAT CAPACITY

POINT NO	TEMP (DEG C)	PRESSURE (KG/CM2)	GRAVITY (DG API)	MEASURED (KJ/KG)	CURVE FIT (KJ/KG)	REL ERR (%)
1	5.0	1.0	30.00	1.75206	1.75207	0.00
2	5.0	50.5	30.00	1.75206	1.75207	0.00
3	5.0	100.0	30.00	1.75206	1.75207	0.00
4	15.0	1.0	30.00	1.79350	1.79350	0.00
5	15.0	50.5	30.00	1.79350	1.79350	0.00
6	15.0	100.0	30.00	1.79350	1.79350	0.00
7	25.0	1.0	30.00	1.83494	1.83493	0.00
8	25.0	50.5	30.00	1.83494	1.83493	0.00
9	25.0	100.0	30.00	1.83494	1.83493	0.00
10	5.0	1.0	35.00	1.79810	1.79811	0.00
11	5.0	50.5	35.00	1.79810	1.79811	0.00
12	5.0	100.0	35.00	1.79810	1.79811	0.00
13	15.0	1.0	35.00	1.83955	1.83955	0.00
14	15.0	50.5	35.00	1.83955	1.83955	0.00
15	15.0	100.0	35.00	1.83955	1.83955	0.00
16	25.0	1.0	35.00	1.88099	1.88098	0.00
17	25.0	50.5	35.00	1.88099	1.88098	0.00
18	25.0	100.0	35.00	1.88099	1.88098	0.00

*** KINEMATIC VISCOSITY DATA

VISCOSITY

POINT NO	TEMP (DEG C)	MEASURED (CS)	CURVE FIT (CS)	REL ERR (%)
1	30.0	6.000	6.000	0.00
2	129.0	1.500	1.500	0.00

BATCH LAUNCHING TOLERANCE CRITERION FOR
API GRAVITY: 1.00

BATCH LAUNCHING TOLERANCE CRITERION FOR

FLUID COMPOSITION: 10.00 %

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 11

INITIAL INLET FLUID CONDITIONS REPORT

*** REPORT INITIAL BATCH LINE FILL ***

DEFAULT LIQUID TYPE ID ----- CRUDE
DEFAULT API ----- 30.7300

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 12

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 13

TLNET DRA PARAMETERS REPORT

DRA SIMULATION STATUS: INACTIVE

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 14

THERE ARE NO TOTALIZED VOLUMES SET FOR THIS NETWORK.

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 15

THERE ARE NO ALARMS SET FOR THIS NETWORK.

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 16

NETWORK CONFIGURATION REPORT

*** LEG DATA

NUMBER OF LEGS: 8

NOMINAL DISTANCE STEP (KM): 4.00

```

-----
LEG   HEAD   TAIL
ID   NODE   NODE
     ID    ID
-----
L1   N02   N03
L2   N03   N05
L3   N06   N07
L4   N07   N09
L5   N10   N11
L6   N11   N13
L7   N13A  N13B
L8   N13D  N13E

```

```

-----
LEG      INSIDE ABS  WALL  DISTANCE
ID  LENGTH DIAM  ROUGH THICKNESS STEP
   ( KM ) ( INCH ) ( MICRON ) ( INCH ) ( KM )
-----
L1    182.73  23.440  45.0000  0.5000  3.97
L2    168.12  23.440  45.0000  0.5000  3.91
L3    125.85  23.440  45.0000  0.5000  3.93
L4     79.35  23.440  45.0000  0.5000  3.97
L5    198.03  23.440  45.0000  0.5000  3.96
L6    180.92  23.440  45.0000  0.5000  3.93
L7     0.05  23.000  45.0000  0.5000  0.05
L8     0.95  23.000  45.0000  0.5000  0.95

```

*** EQUIPMENT DATA

NUMBER OF EQUIPMENT DEVICES: 7

```

-----
EQP  UPSIDE DOWNSIDE  TYPE OF  SETPOINT/
ID  NODE ID  NODE ID  EQUIPMENT  CONSTRAINTS
-----
BLKVCOT N13E  N13F  BLOCK VALVE  PERCENT OPEN
BLKVST  N13   N13A  BLOCK VALVE  PERCENT OPEN
CVBINA  N13B  N13C  RESISTANCE  RESISTANCE
METERBIN N13C  N13D  RESISTANCE  RESISTANCE
PUMPIP2 N05   N06   PUMP        FREE FLOW

```

			MIN UP PRES	
			PERCENT OPEN	
PUMPIP4	N09	N10	PUMP	FREE FLOW
			MIN UP PRES	
			PERCENT OPEN	
PUMPVAD	N01	N02	PUMP	FREE FLOW
			MIN UP PRES	
			PERCENT OPEN	

 VALVE PHYSICAL CHARACTERISTIC DATA

EQP ID	TYPE OF VALVE	FULLY OPEN Cv (GPM/PSI)	VALVE SIZE (INCH)
BLKVST	BLOCK VALVE	53500.	24.000
BLKVCOT	BLOCK VALVE	53500.	24.000

*** EXTERNAL REGULATOR DATA

NUMBER OF EXTERNAL REGULATORS: 3

XRG ID	NODE ID	TYPE OF EXTERNAL REGULATOR	SETPOINT/ CONSTRAINTS
BINA	N13F	DELIVERY MIN PRES	CHECK VALVE
SRV	N13C	DELIVERY MIN PRES	CHECK VALVE
VADINAR	N01	SUPPLY	MAX FLOW

*** SINGLE PUMP DATA

NUMBER OF SINGLE PUMPS: 3

PUMP ID	PUMP PERF TYPE ID	TURBINE TYPE ID
PUMPIP2	0	0

PUMPIP4 0 0
PUMPVAD 0 0

```

-----
PUMP  PUMP  VLV LOSS ADB. EFC MCH. EFC AUX LOAD
ID  CATEGORY  (FT)  (PERCNT) (PERCNT) ( MW )
-----
PUMPVAD  GENERIC  N/A    100.00  100.00  0.00
PUMPIP2  GENERIC  N/A    100.00  100.00  0.00
PUMPIP4  GENERIC  N/A    100.00  100.00  0.00

```

*** NODE DATA

NUMBER OF NODES: 16

```

-----
NODE  ELEVATION          CONNECTED
ID  ( M )  LEGS / EQUIPMENT / EXTERNAL REGULATORS
-----
N01    10.00  EQP IDS: PUMPVAD
          XRG IDS: VADINAR
N02    10.00  LEG IDS: L1
          EQP IDS: PUMPVAD
N03    154.15  LEG IDS: L1  L2
N05    19.49  LEG IDS: L2
          EQP IDS: PUMPIP2
N06    19.49  LEG IDS: L3
          EQP IDS: PUMPIP2
N07    396.38  LEG IDS: L3  L4
N09    416.05  LEG IDS: L4
          EQP IDS: PUMPIP4
N10    416.05  LEG IDS: L5
          EQP IDS: PUMPIP4
N11    408.16  LEG IDS: L5  L6
N13    400.00  LEG IDS: L6
          EQP IDS: BLKVST
N13A   400.00  LEG IDS: L7
          EQP IDS: BLKVST
N13B   400.00  LEG IDS: L7
          EQP IDS: CVBINA
N13C   400.00  EQP IDS: CVBINA  METERBIN
          XRG IDS: SRV
N13D   400.00  LEG IDS: L8

```

EQP IDS: METERBIN
 N13E 400.00 LEG IDS: L8
 EQP IDS: BLKVCOT
 N13F 400.00 EQP IDS: BLKVCOT
 XRG IDS: BINA

*** USER-DEFINED LINE DATA

NUMBER OF USER-LINES: 1

USER-LINE: MAIN

COMP TYPE	COMP ID	MILEPOST (KM)	DISTANCE (KM)	VOLUME (M3)
XRG	VADINAR	0.0	0.0	0.000
NOD	N01	0.0	0.0	0.000
EQP	PUMPVAD	0.0	0.0	0.000
NOD	N02	0.0	0.0	0.000
LEG	L1	0.0	0.0	0.000
NOD	N03	182.7	182.7	50.878
LEG	L2	182.7	182.7	50.878
NOD	N05	350.9	350.9	97.688
EQP	PUMPIP2	350.9	350.9	97.688
NOD	N06	350.9	350.9	97.688
LEG	L3	350.9	350.9	97.688
NOD	N07	476.7	476.7	132.730
LEG	L4	476.7	476.7	132.730
NOD	N09	556.0	556.0	154.822
EQP	PUMPIP4	556.0	556.0	154.822
NOD	N10	556.0	556.0	154.822
LEG	L5	556.0	556.0	154.822
NOD	N11	754.1	754.1	209.960
LEG	L6	754.1	754.1	209.960
NOD	N13	935.0	935.0	260.335
EQP	BLKVST	935.0	935.0	260.335
NOD	N13A	935.0	935.0	260.335
LEG	L7	935.0	935.0	260.335
NOD	N13B	935.1	935.1	260.348
EQP	CVBINA	935.1	935.1	260.348
NOD	N13C	935.1	935.1	260.348
EQP	METERBIN	935.1	935.1	260.348
NOD	N13D	935.1	935.1	260.348

LEG	L8	935.1	935.1	260.348
NOD	N13E	936.0	936.0	260.603
EQP	BLKVCOT	936.0	936.0	260.603
NOD	N13F	936.0	936.0	260.603
XRG	BINA	936.0	936.0	260.603

*** ELEVATION PROFILE DATA

NUMBER OF USER LINE ELEVATION PROFILES: 1

USER LINE: MAIN

MILEPOST ELEVATION CRITICAL POINT
(KM) (M) (0=NO,1=YES)

0.00	10.0	0
100.00	60.0	0
125.00	130.0	0
150.00	100.0	0
160.00	160.0	0
180.00	160.0	0
250.00	10.0	0
320.00	10.0	0
385.00	30.0	0
400.00	90.0	0
405.00	70.0	0
460.00	280.0	0
475.00	410.0	0
490.00	290.0	0
500.00	330.0	0
510.00	370.0	0
515.00	290.0	0
525.00	370.0	0
530.00	310.0	0
550.00	410.0	0
570.00	430.0	0
580.00	390.0	0
615.00	510.0	0
660.00	470.0	0
675.00	530.0	0
690.00	470.0	0
710.00	490.0	0
720.00	410.0	0

730.00 430.0 0
 745.00 390.0 0
 770.00 440.0 0
 780.00 440.0 0
 790.00 380.0 0
 810.00 380.0 0
 830.00 460.0 0
 840.00 390.0 0
 855.00 510.0 0
 890.00 530.0 0
 920.00 390.0 0
 925.00 400.0 0
 930.00 390.0 0
 935.00 400.0 0
 936.00 400.0 0

SYSTEM-WIDE FLUID CONDITIONS REPORT

SYSTEM-WIDE FLUID TEMPERATURE (DEG C): 20.00

LIQUID TYPE ID: CRUDE

SYSTEM-WIDE FLUID API GRAV (DG API): 30.73

INITIAL MODES/SETPOINTS/CONSTRAINTS REPORT

*** EQUIPMENT DATA

EQP ID	TYPE OF EQUIPMENT	INITIAL MODE	SETPOINT/ CONSTRAINTS	SETPT/CNSTRT VALUE
BLKVCOT	BLOCK VALVE	BLOCK VALVE	*PERCENT OPEN	100.000
BLKVST	BLOCK VALVE	BLOCK VALVE	*PERCENT OPEN	100.000
CVBINA	RESISTANCE	RESISTANCE	*RESISTANCE	0.00

KQ2=ABS(PU2-PD2)

METERBIN RESISTANCE RESISTANCE *RESISTANCE 0.00
 KQ2=ABS(PU2-PD2)
 PUMPIP2 PUMP MIN PU MIN UP PRES 5.00 A)(KG
 PERCENT OPEN 1.000
 PUMPIP4 PUMP MIN PU MIN UP PRES 5.00 A)(KG
 PERCENT OPEN 1.000
 PUMPVAD PUMP MIN PU MIN UP PRES 2.00 A)(KG
 PERCENT OPEN 1.000

NOTE: * INDICATES CONSTRAINT IS FORCED BY PROGRAM

*** EXTERNAL REGULATOR DATA

XRG ID	TYPE OF EXTERNAL REGULATOR	INITIAL MODE	SETPOINT/CONSTRAINTS	SETPT/CNSTRT VALUE
BINA	DELIVERY	MIN PRES	MIN PRES	2.00 A)(KG
SRV	DELIVERY	MIN PRES	MIN PRES	12.00 A)(KG
VADINAR	SUPPLY	MAX FLOW	MAX FLOW	862.0 (M3/HR)

TLNET VERSION 5.1 A PROPRIETARY PRODUCT OF SS-I PAGE 19

TLNET CASE SIZE REPORT AND MAXIMUM SIZES
 =====

NUMBER OF EQUIPMENT	7	100
NUMBER OF LEGS	8	75
NUMBER OF NODES	16	500
NUMBER OF EXTERNAL REGULATORS	3	100
NUMBER OF KNOTS	247	800
NUMBER OF XREG CONSTRAINTS	5	600
NUMBER OF EQUIP CONSTRAINTS	13	500
NUMBER OF EQUIP VARIABLE DATA	33	700
NUMBER OF USER LINES	1	30
NUMBER OF TANKS	0	50

***** STEADY STATE CONVERGENCE SUMMARY

ITERATION -----TOLERANCE VALUES----- ERROR COMPONENT
NUMBER CONVERGENCE HYDRAULIC TEMPERATURE NAME
(TYPE)

	iiiiiiii	iiiiiiiiii	iiiiiiiiii	iiiiiiiiii	iiiiiiiiii	
1	.10000E-03	.10610E+01	.00000E+00	SRV	(XREG)	
2	.10000E-03	.10998E+01	.00000E+00	SRV	(XREG)	
3	.10000E-03	.78967E+00	.00000E+00	SRV	(XREG)	
4	.10000E-03	.31250E+00	.00000E+00	N01	(NODE)	
5	.10000E-03	.45455E+00	.00000E+00	N01	(NODE)	
6	.10000E-03	.83333E+00	.00000E+00	N01	(NODE)	
7	.10000E-03	.28619E+01	.00000E+00	N01	(NODE)	
8	.10000E-03	.14449E+00	.00000E+00	N07	(NODE)	
9	.10000E-03	.64198E-03	.00000E+00	SRV	(XREG)	
10	.10000E-03	.83517E-05	.00000E+00	N13D	(NODE)	

----- MODE CHANGES -----

10	XREG	SRV	FROM: MIN PRES	TO: CLOSED	
11	.10000E-03	.19717E-06	.00000E+00	N10	(NODE)
12	.10000E-03	.17004E+03	.00000E+00	SRV	(XREG)
13	.10000E-03	.36312E+00	.00000E+00	N13C	(NODE)
14	.10000E-03	.28653E-03	.00000E+00	N10	(NODE)
15	.10000E-03	.19754E-04	.00000E+00	N10	(NODE)
16	.10000E-03	.14444E-06	.00000E+00	N10	(NODE)

TLNET VERSION 5.1

A PROPRIETARY PRODUCT OF SS-I

PAGE 20

REFERENCE PRESSURE = 0.00 A)(KG

REFERENCE TEMPERATURE = 15.56 (DEG C)

LEG HYDRAULIC DETAILED REPORT

TIME = 0.000 (MINS)

USER LINE: MAIN

DISTANCE PRESSURE MAX-PRES MIN-PRES DENSITY VELOCITY FLOW TEMP HEAD ELEV API
VISCOSITY FRICTION
(KM) A)(KG A)(KG A)(KG (KG/M3) (M/S) (M3/HR) (DEG C) (M) (M) GRAV FACTOR

LEG: L1 23.440 IN. D. (INCH) FROM NODE: N02 TO NODE: N03

0.00	44.38	59.48	42.59	871.7731	0.86	862.00	20.00	531.2	10.0	30.73	.75620E+01	0.19864E-01
3.97	43.77	59.58	42.21	871.7368	0.86	862.00	20.00	526.2	12.0	30.73	.75620E+01	0.19863E-01
7.94	43.16	59.68	41.83	871.7004	0.86	862.00	20.00	521.2	14.0	30.73	.75620E+01	0.19863E-01
11.92	42.55	59.78	41.45	871.6641	0.86	862.00	20.00	516.2	16.0	30.73	.75620E+01	0.19863E-01
15.89	41.94	59.88	41.07	871.6278	0.86	862.00	20.00	511.3	17.9	30.73	.75620E+01	0.19863E-01
19.86	41.33	59.98	40.68	871.5915	0.86	862.00	20.00	506.3	19.9	30.73	.75620E+01	0.19862E-01
23.83	40.73	60.08	40.09	871.5552	0.86	862.00	20.00	501.3	21.9	30.73	.75620E+01	0.19862E-01
27.81	40.12	60.18	39.50	871.5189	0.86	862.00	20.00	496.3	23.9	30.73	.75620E+01	0.19862E-01
31.78	39.51	60.28	38.90	871.4825	0.86	862.00	20.00	491.3	25.9	30.73	.75620E+01	0.19862E-01
35.75	38.90	60.38	38.31	871.4463	0.86	862.00	20.00	486.4	27.9	30.73	.75620E+01	0.19862E-01
39.72	38.29	60.48	37.72	871.4100	0.86	862.00	20.00	481.4	29.9	30.73	.75620E+01	0.19861E-01
43.70	37.68	60.58	37.12	871.3737	0.86	862.00	20.00	476.4	31.8	30.73	.75620E+01	0.19861E-01
47.67	37.07	60.68	36.53	871.3373	0.86	862.00	20.00	471.4	33.8	30.73	.75620E+01	0.19861E-01
51.64	36.47	60.78	35.94	871.3010	0.86	862.00	20.00	466.4	35.8	30.73	.75620E+01	0.19861E-01
55.61	35.86	60.88	35.35	871.2647	0.86	862.00	20.00	461.4	37.8	30.73	.75620E+01	0.19860E-01
59.59	35.25	60.98	34.75	871.2284	0.86	862.00	20.00	456.4	39.8	30.73	.75620E+01	0.19860E-01
63.56	34.64	61.08	34.16	871.1921	0.86	862.00	20.00	451.5	41.8	30.73	.75620E+01	0.19860E-01
67.53	34.03	61.18	33.57	871.1558	0.86	862.00	20.00	446.5	43.8	30.73	.75620E+01	0.19860E-01
71.50	33.42	61.28	32.97	871.1194	0.86	862.00	20.00	441.5	45.8	30.73	.75620E+01	0.19859E-01
75.48	32.81	61.38	32.38	871.0831	0.86	862.00	20.00	436.5	47.7	30.73	.75620E+01	0.19859E-01
79.45	32.20	61.48	31.79	871.0468	0.86	862.00	20.00	431.5	49.7	30.73	.75620E+01	0.19859E-01

83.42	31.60	61.58	31.19	871.0105	0.86	862.00	20.00	426.5	51.7	30.73	.75620E+01	0.19859E-01
87.39	30.99	61.68	30.60	870.9742	0.86	862.00	20.00	421.5	53.7	30.73	.75620E+01	0.19859E-01
91.37	30.38	61.78	30.01	870.9379	0.86	862.00	20.00	416.5	55.7	30.73	.75620E+01	0.19858E-01
95.34	29.77	61.88	29.41	870.9016	0.86	862.00	20.00	411.5	57.7	30.73	.75620E+01	0.19858E-01
99.31	29.16	61.98	28.82	870.8653	0.86	862.00	20.00	406.5	59.7	30.73	.75620E+01	0.19858E-01
103.28	27.89	61.42	27.57	870.7899	0.86	862.00	20.00	401.6	69.2	30.73	.75620E+01	0.19857E-01
107.26	26.49	60.73	26.18	870.7061	0.86	862.00	20.00	396.6	80.3	30.73	.75620E+01	0.19857E-01
111.23	25.09	60.03	24.79	870.6224	0.86	862.00	20.00	391.6	91.4	30.73	.75620E+01	0.19856E-01
115.20	23.68	59.33	23.41	870.5387	0.86	862.00	20.00	386.6	102.6	30.73	.75620E+01	0.19856E-01
119.17	22.28	58.64	22.02	870.4550	0.86	862.00	20.00	381.6	113.7	30.73	.75620E+01	0.19855E-01
123.14	20.87	57.94	20.63	870.3713	0.86	862.00	20.00	376.6	124.8	30.73	.75620E+01	0.19855E-01
127.12	20.21	57.98	19.98	870.3316	0.86	862.00	20.00	371.6	127.5	30.73	.75620E+01	0.19855E-01
131.09	20.18	58.67	19.97	870.3303	0.86	862.00	20.00	366.6	122.7	30.73	.75620E+01	0.19855E-01
135.06	20.16	59.36	19.97	870.3290	0.86	862.00	20.00	361.6	117.9	30.73	.75620E+01	0.19855E-01
139.03	20.14	60.05	19.96	870.3278	0.86	862.00	20.00	356.6	113.2	30.73	.75620E+01	0.19855E-01
143.01	20.12	60.74	19.95	870.3264	0.86	862.00	20.00	351.6	108.4	30.73	.75620E+01	0.19855E-01
146.98	20.10	61.43	19.95	870.3251	0.86	862.00	20.00	346.5	103.6	30.73	.75620E+01	0.19855E-01
150.95	19.48	61.52	19.34	870.2883	0.86	862.00	20.00	341.5	105.7	30.73	.75620E+01	0.19854E-01
154.92	16.97	59.71	16.85	870.1388	0.86	862.00	20.00	336.6	129.5	30.73	.75620E+01	0.19853E-01
158.90	14.46	57.91	14.36	869.9893	0.86	862.00	20.00	331.6	153.4	30.73	.75620E+01	0.19852E-01
162.87	13.45	57.60	13.36	869.9290	0.86	862.00	20.00	326.6	160.0	30.73	.75620E+01	0.19852E-01
166.84	13.01	57.87	12.94	869.9030	0.86	862.00	20.00	321.5	160.0	30.73	.75620E+01	0.19852E-01
170.81	12.58	58.15	12.52	869.8770	0.86	862.00	20.00	316.5	160.0	30.73	.75620E+01	0.19852E-01
174.79	12.14	58.42	12.10	869.8510	0.86	862.00	20.00	311.5	160.0	30.73	.75620E+01	0.19852E-01
178.76	11.70	58.70	11.68	869.8250	0.86	862.00	20.00	306.5	160.0	30.73	.75620E+01	0.19851E-01
182.73	11.77	59.48	11.77	869.8293	0.86	862.00	20.00	301.5	154.1	30.73	.75620E+01	0.19851E-01

LEG: L2 23.440 IN. D. (INCH) FROM NODE: N03 TO NODE: N05

182.73	11.77	59.48	11.77	869.8293	0.86	862.00	20.00	301.5	154.1	30.73	.75620E+01	0.19851E-01
186.64	12.07	59.94	12.07	869.8470	0.86	862.00	20.00	296.5	145.8	30.73	.75620E+01	0.19852E-01

190.55	12.37	60.40	12.37	869.8649	0.86	862.00	20.00	291.6	137.4	30.73	.75620E+01	0.19852E-01
194.46	12.67	60.85	12.67	869.8826	0.86	862.00	20.00	286.6	129.0	30.73	.75620E+01	0.19852E-01
198.37	12.97	61.31	12.97	869.9003	0.86	862.00	20.00	281.7	120.6	30.73	.75620E+01	0.19852E-01
202.28	13.27	61.77	13.27	869.9182	0.86	862.00	20.00	276.7	112.3	30.73	.75620E+01	0.19852E-01
206.19	13.57	62.23	13.57	869.9359	0.86	862.00	20.00	271.8	103.9	30.73	.75620E+01	0.19852E-01
210.10	13.86	62.68	13.86	869.9537	0.86	862.00	20.00	266.8	95.5	30.73	.75620E+01	0.19852E-01
214.01	14.16	63.14	14.16	869.9716	0.86	862.00	20.00	261.9	87.1	30.73	.75620E+01	0.19852E-01
217.92	14.46	63.60	14.46	869.9893	0.86	862.00	20.00	256.9	78.7	30.73	.75620E+01	0.19852E-01
221.83	14.76	64.06	14.76	870.0071	0.86	862.00	20.00	252.0	70.4	30.73	.75620E+01	0.19853E-01
225.74	15.06	64.52	15.06	870.0249	0.86	862.00	20.00	247.0	62.0	30.73	.75620E+01	0.19853E-01
229.65	15.36	64.97	15.36	870.0427	0.86	862.00	20.00	242.1	53.6	30.73	.75620E+01	0.19853E-01
233.56	15.66	65.43	15.66	870.0605	0.86	862.00	20.00	237.2	45.2	30.73	.75620E+01	0.19853E-01
237.47	15.96	65.89	15.96	870.0784	0.86	862.00	20.00	232.2	36.9	30.73	.75620E+01	0.19853E-01
241.38	16.25	66.35	16.25	870.0961	0.86	862.00	20.00	227.3	28.5	30.73	.75620E+01	0.19853E-01
245.29	16.55	66.81	16.55	870.1140	0.86	862.00	20.00	222.3	20.1	30.73	.75620E+01	0.19853E-01
249.20	16.85	67.26	16.85	870.1317	0.86	862.00	20.00	217.4	11.7	30.73	.75620E+01	0.19853E-01
253.11	16.57	67.14	16.57	870.1151	0.86	862.00	20.00	212.4	10.0	30.73	.75620E+01	0.19853E-01
257.02	16.14	66.87	16.14	870.0895	0.86	862.00	20.00	207.5	10.0	30.73	.75620E+01	0.19853E-01
260.93	15.71	66.59	15.71	870.0638	0.86	862.00	20.00	202.6	10.0	30.73	.75620E+01	0.19853E-01
264.84	15.28	66.32	15.28	870.0383	0.86	862.00	20.00	197.6	10.0	30.73	.75620E+01	0.19853E-01
268.75	14.85	66.05	14.85	870.0127	0.86	862.00	20.00	192.7	10.0	30.73	.75620E+01	0.19853E-01
272.66	14.42	65.77	14.42	869.9871	0.86	862.00	20.00	187.8	10.0	30.73	.75620E+01	0.19852E-01
276.56	13.99	65.50	13.99	869.9615	0.86	862.00	20.00	182.8	10.0	30.73	.75620E+01	0.19852E-01
280.47	13.56	65.23	13.56	869.9359	0.86	862.00	20.00	177.9	10.0	30.73	.75620E+01	0.19852E-01
284.38	13.13	64.95	13.13	869.9103	0.86	862.00	20.00	172.9	10.0	30.73	.75620E+01	0.19852E-01
288.29	12.70	64.68	12.70	869.8847	0.86	862.00	20.00	168.0	10.0	30.73	.75620E+01	0.19852E-01
292.20	12.27	64.41	12.27	869.8591	0.86	862.00	20.00	163.1	10.0	30.73	.75620E+01	0.19852E-01
296.11	11.84	64.13	11.84	869.8335	0.86	862.00	20.00	158.1	10.0	30.73	.75620E+01	0.19851E-01
300.02	11.41	63.86	11.41	869.8079	0.86	862.00	20.00	153.2	10.0	30.73	.75620E+01	0.19851E-01
303.93	10.99	63.59	10.99	869.7823	0.86	862.00	20.00	148.2	10.0	30.73	.75620E+01	0.19851E-01
307.84	10.56	63.31	10.56	869.7567	0.86	862.00	20.00	143.3	10.0	30.73	.75620E+01	0.19851E-01

311.75	10.13	63.04	10.13	869.7311	0.86	862.00	20.00	138.4	10.0	30.73	.75620E+01	0.19851E-01
315.66	9.70	62.77	9.70	869.7054	0.86	862.00	20.00	133.4	10.0	30.73	.75620E+01	0.19851E-01
319.57	9.27	62.49	9.27	869.6799	0.86	862.00	20.00	128.5	10.0	30.73	.75620E+01	0.19851E-01
323.48	8.74	62.13	8.74	869.6487	0.86	862.00	20.00	123.5	11.1	30.73	.75620E+01	0.19850E-01
327.39	8.21	61.75	8.21	869.6169	0.86	862.00	20.00	118.6	12.3	30.73	.75620E+01	0.19850E-01
331.30	7.67	61.37	7.67	869.5851	0.86	862.00	20.00	113.6	13.5	30.73	.75620E+01	0.19850E-01
335.21	7.14	60.99	7.14	869.5533	0.86	862.00	20.00	108.7	14.7	30.73	.75620E+01	0.19850E-01
339.12	6.60	60.61	6.60	869.5214	0.86	862.00	20.00	103.8	15.9	30.73	.75620E+01	0.19850E-01
343.03	6.07	60.24	6.07	869.4896	0.86	862.00	20.00	98.8	17.1	30.73	.75620E+01	0.19849E-01
346.94	5.53	59.86	5.53	869.4578	0.86	862.00	20.00	93.9	18.3	30.73	.75620E+01	0.19849E-01
350.85	5.00	59.48	5.00	869.4259	0.86	862.00	20.00	88.9	19.5	30.73	.75620E+01	0.19849E-01

LEG: L3 23.440 IN. D. (INCH) FROM NODE: N06 TO NODE: N07

350.85	62.04	80.27	59.48	872.8281	0.86	862.00	20.00	742.5	19.5	30.73	.75620E+01	0.19870E-01
354.78	61.51	79.63	59.13	872.7960	0.86	862.00	20.00	737.6	20.7	30.73	.75620E+01	0.19870E-01
358.72	60.97	78.99	58.59	872.7640	0.86	862.00	20.00	732.7	21.9	30.73	.75620E+01	0.19870E-01
362.65	60.43	78.35	58.06	872.7321	0.86	862.00	20.00	727.8	23.1	30.73	.75620E+01	0.19869E-01
366.58	59.90	77.80	57.52	872.7000	0.86	862.00	20.00	722.9	24.3	30.73	.75620E+01	0.19869E-01
370.51	59.36	77.50	56.98	872.6680	0.86	862.00	20.00	718.0	25.5	30.73	.75620E+01	0.19869E-01
374.45	58.83	77.21	56.45	872.6359	0.86	862.00	20.00	713.1	26.8	30.73	.75620E+01	0.19869E-01
378.38	58.29	76.91	55.91	872.6039	0.86	862.00	20.00	708.2	28.0	30.73	.75620E+01	0.19869E-01
382.31	57.75	76.61	55.38	872.5719	0.86	862.00	20.00	703.2	29.2	30.73	.75620E+01	0.19868E-01
386.25	56.82	75.91	54.44	872.5159	0.86	862.00	20.00	698.4	35.0	30.73	.75620E+01	0.19868E-01
390.18	55.01	74.34	52.64	872.4083	0.86	862.00	20.00	693.5	50.7	30.73	.75620E+01	0.19867E-01
394.11	53.21	72.78	50.83	872.3006	0.86	862.00	20.00	688.6	66.4	30.73	.75620E+01	0.19867E-01
398.04	51.41	71.21	49.03	872.1929	0.86	862.00	20.00	683.8	82.2	30.73	.75620E+01	0.19866E-01
401.98	50.99	71.02	48.61	872.1677	0.86	862.00	20.00	678.8	82.1	30.73	.75620E+01	0.19866E-01
405.91	51.31	71.58	48.93	872.1868	0.86	862.00	20.00	673.9	73.5	30.73	.75620E+01	0.19866E-01
409.84	49.57	70.08	47.19	872.0829	0.86	862.00	20.00	669.0	88.5	30.73	.75620E+01	0.19865E-01
413.78	47.83	68.59	45.45	871.9791	0.86	862.00	20.00	664.1	103.5	30.73	.75620E+01	0.19865E-01

417.71	46.09	68.31	43.71	871.8752	0.86	862.00	20.00	659.3	118.5	30.73	.75620E+01	0.19864E-01
421.64	44.35	68.03	41.97	871.7714	0.86	862.00	20.00	654.4	133.5	30.73	.75620E+01	0.19864E-01
425.57	42.61	67.75	40.23	871.6675	0.86	862.00	20.00	649.5	148.6	30.73	.75620E+01	0.19863E-01
429.51	40.87	67.46	38.49	871.5638	0.86	862.00	20.00	644.6	163.6	30.73	.75620E+01	0.19862E-01
433.44	39.13	67.18	36.75	871.4600	0.86	862.00	20.00	639.7	178.6	30.73	.75620E+01	0.19862E-01
437.37	37.39	66.90	35.01	871.3563	0.86	862.00	20.00	634.8	193.6	30.73	.75620E+01	0.19861E-01
441.31	35.65	66.62	33.27	871.2525	0.86	862.00	20.00	629.9	208.6	30.73	.75620E+01	0.19860E-01
445.24	33.91	66.33	31.53	871.1487	0.86	862.00	20.00	625.0	223.6	30.73	.75620E+01	0.19860E-01
449.17	32.17	66.05	29.80	871.0450	0.86	862.00	20.00	620.1	238.7	30.73	.75620E+01	0.19859E-01
453.10	30.44	65.77	28.06	870.9413	0.86	862.00	20.00	615.2	253.7	30.73	.75620E+01	0.19858E-01
457.04	28.70	65.48	26.32	870.8377	0.86	862.00	20.00	610.3	268.7	30.73	.75620E+01	0.19858E-01
460.97	26.55	64.79	24.17	870.7096	0.86	862.00	20.00	605.3	288.4	30.73	.75620E+01	0.19857E-01
464.90	23.15	62.84	20.77	870.5071	0.86	862.00	20.00	600.5	322.5	30.73	.75620E+01	0.19856E-01
468.84	19.75	60.90	17.38	870.3046	0.86	862.00	20.00	595.5	356.6	30.73	.75620E+01	0.19854E-01
472.77	16.36	58.95	13.98	870.1022	0.86	862.00	20.00	590.6	390.7	30.73	.75620E+01	0.19853E-01
476.70	15.43	59.48	13.05	870.0469	0.86	862.00	20.00	585.7	396.4	30.73	.75620E+01	0.19853E-01

LEG: L4 23.440 IN. D. (INCH) FROM NODE: N07 TO NODE: N09

476.70	15.43	59.48	13.05	870.0469	0.86	862.00	20.00	585.7	396.4	30.73	.75620E+01	0.19853E-01
480.67	17.75	62.34	15.49	870.1853	0.86	862.00	20.00	580.6	364.6	30.73	.75620E+01	0.19854E-01
484.64	20.08	65.19	17.94	870.3239	0.86	862.00	20.00	575.6	332.9	30.73	.75620E+01	0.19855E-01
488.60	22.40	68.05	20.38	870.4624	0.86	862.00	20.00	570.5	301.2	30.73	.75620E+01	0.19855E-01
492.57	22.04	68.21	20.14	870.4410	0.86	862.00	20.00	565.5	300.3	30.73	.75620E+01	0.19855E-01
496.54	20.23	66.91	18.44	870.3328	0.86	862.00	20.00	560.5	316.2	30.73	.75620E+01	0.19855E-01
500.51	18.41	65.61	16.74	870.2246	0.86	862.00	20.00	555.6	332.0	30.73	.75620E+01	0.19854E-01
504.47	16.59	64.31	15.05	870.1164	0.86	862.00	20.00	550.6	347.9	30.73	.75620E+01	0.19853E-01
508.44	14.78	63.01	13.35	870.0082	0.86	862.00	20.00	545.6	363.8	30.73	.75620E+01	0.19853E-01
512.41	17.15	65.92	15.84	870.1495	0.86	862.00	20.00	540.5	331.5	30.73	.75620E+01	0.19853E-01
516.38	19.36	68.66	18.17	870.2814	0.86	862.00	20.00	535.5	301.0	30.73	.75620E+01	0.19854E-01
520.34	16.17	65.98	15.10	870.0909	0.86	862.00	20.00	530.5	332.7	30.73	.75620E+01	0.19853E-01

524.31	12.97	63.29	12.02	869.9006	0.86	862.00	20.00	525.6	364.5	30.73	.75620E+01	0.19852E-01
528.28	15.48	66.33	14.64	870.0497	0.86	862.00	20.00	520.5	330.7	30.73	.75620E+01	0.19853E-01
532.24	15.86	67.24	15.15	870.0727	0.86	862.00	20.00	515.5	321.2	30.73	.75620E+01	0.19853E-01
536.21	13.70	65.60	13.10	869.9440	0.86	862.00	20.00	510.5	341.1	30.73	.75620E+01	0.19852E-01
540.18	11.54	63.95	11.06	869.8152	0.86	862.00	20.00	505.5	360.9	30.73	.75620E+01	0.19851E-01
544.15	9.38	62.30	9.02	869.6866	0.86	862.00	20.00	500.5	380.7	30.73	.75620E+01	0.19851E-01
548.11	7.22	60.66	6.98	869.5579	0.86	862.00	20.00	495.5	400.6	30.73	.75620E+01	0.19850E-01
552.08	5.78	59.74	5.66	869.4724	0.86	862.00	20.00	490.5	412.1	30.73	.75620E+01	0.19849E-01
556.05	5.00	59.48	5.00	869.4259	0.86	862.00	20.00	485.5	416.0	30.73	.75620E+01	0.19849E-01

LEG: L5 23.440 IN. D. (INCH) FROM NODE: N10 TO NODE: N11

556.05	48.23	59.48	32.35	872.0033	0.86	862.00	20.00	981.3	416.0	30.73	.75620E+01	0.19865E-01
560.01	47.45	59.12	31.95	871.9568	0.86	862.00	20.00	976.4	420.0	30.73	.75620E+01	0.19865E-01
563.97	46.67	58.76	31.55	871.9103	0.86	862.00	20.00	971.4	424.0	30.73	.75620E+01	0.19864E-01
567.93	45.89	58.40	31.15	871.8638	0.86	862.00	20.00	966.5	427.9	30.73	.75620E+01	0.19864E-01
571.89	45.94	58.87	31.57	871.8664	0.86	862.00	20.00	961.5	422.4	30.73	.75620E+01	0.19864E-01
575.85	46.89	60.24	32.89	871.9229	0.86	862.00	20.00	956.5	406.6	30.73	.75620E+01	0.19864E-01
579.81	47.83	61.60	34.21	871.9794	0.86	862.00	20.00	951.5	390.8	30.73	.75620E+01	0.19865E-01
583.77	46.34	60.53	33.10	871.8901	0.86	862.00	20.00	946.5	402.9	30.73	.75620E+01	0.19864E-01
587.73	44.72	59.33	31.86	871.7936	0.86	862.00	20.00	941.6	416.5	30.73	.75620E+01	0.19864E-01
591.69	43.10	58.13	30.62	871.6971	0.86	862.00	20.00	936.7	430.1	30.73	.75620E+01	0.19863E-01
595.65	41.49	56.93	29.38	871.6005	0.86	862.00	20.00	931.8	443.7	30.73	.75620E+01	0.19862E-01
599.62	39.87	55.73	28.14	871.5041	0.86	862.00	20.00	926.8	457.3	30.73	.75620E+01	0.19862E-01
603.58	38.25	54.53	26.90	871.4075	0.86	862.00	20.00	921.9	470.8	30.73	.75620E+01	0.19861E-01
607.54	36.63	53.33	25.66	871.3111	0.86	862.00	20.00	916.9	484.4	30.73	.75620E+01	0.19861E-01
611.50	35.02	52.14	24.42	871.2147	0.86	862.00	20.00	912.0	498.0	30.73	.75620E+01	0.19860E-01
615.46	33.57	51.11	23.36	871.1285	0.86	862.00	20.00	907.1	509.6	30.73	.75620E+01	0.19860E-01
619.42	33.44	51.40	23.61	871.1208	0.86	862.00	20.00	902.1	506.1	30.73	.75620E+01	0.19859E-01
623.38	33.32	51.70	23.86	871.1132	0.86	862.00	20.00	897.1	502.6	30.73	.75620E+01	0.19859E-01
627.34	33.19	51.99	24.11	871.1056	0.86	862.00	20.00	892.1	499.0	30.73	.75620E+01	0.19859E-01

631.30	33.06	52.28	24.36	871.0979	0.86	862.00	20.00	887.1	495.5	30.73	.75620E+01	0.19859E-01
635.26	32.93	52.58	24.61	871.0903	0.86	862.00	20.00	882.1	492.0	30.73	.75620E+01	0.19859E-01
639.22	32.80	52.87	24.86	871.0826	0.86	862.00	20.00	877.1	488.5	30.73	.75620E+01	0.19859E-01
643.18	32.68	53.16	25.11	871.0750	0.86	862.00	20.00	872.1	484.9	30.73	.75620E+01	0.19859E-01
647.14	32.55	53.46	25.35	871.0674	0.86	862.00	20.00	867.2	481.4	30.73	.75620E+01	0.19859E-01
651.10	32.42	53.75	25.60	871.0598	0.86	862.00	20.00	862.2	477.9	30.73	.75620E+01	0.19859E-01
655.06	32.29	54.04	25.85	871.0521	0.86	862.00	20.00	857.2	474.4	30.73	.75620E+01	0.19859E-01
659.02	32.16	54.34	26.08	871.0444	0.86	862.00	20.00	852.2	470.9	30.73	.75620E+01	0.19859E-01
662.98	30.77	53.36	24.80	870.9611	0.86	862.00	20.00	847.2	481.9	30.73	.75620E+01	0.19858E-01
666.95	28.95	51.96	23.10	870.8529	0.86	862.00	20.00	842.3	497.8	30.73	.75620E+01	0.19858E-01
670.91	27.14	50.56	21.40	870.7448	0.86	862.00	20.00	837.3	513.6	30.73	.75620E+01	0.19857E-01
674.87	25.32	49.17	19.70	870.6367	0.86	862.00	20.00	832.4	529.5	30.73	.75620E+01	0.19856E-01
678.83	26.18	50.44	20.66	870.6874	0.86	862.00	20.00	827.4	514.7	30.73	.75620E+01	0.19857E-01
682.79	27.12	51.81	21.72	870.7437	0.86	862.00	20.00	822.3	498.9	30.73	.75620E+01	0.19857E-01
686.75	28.06	53.18	22.78	870.7999	0.86	862.00	20.00	817.3	483.0	30.73	.75620E+01	0.19857E-01
690.71	28.70	54.24	23.52	870.8378	0.86	862.00	20.00	812.3	470.7	30.73	.75620E+01	0.19858E-01
694.67	27.92	53.88	22.86	870.7914	0.86	862.00	20.00	807.3	474.7	30.73	.75620E+01	0.19857E-01
698.63	27.14	53.52	22.19	870.7449	0.86	862.00	20.00	802.4	478.6	30.73	.75620E+01	0.19857E-01
702.59	26.36	53.16	21.53	870.6984	0.86	862.00	20.00	797.4	482.6	30.73	.75620E+01	0.19857E-01
706.55	25.58	52.80	20.86	870.6520	0.86	862.00	20.00	792.4	486.6	30.73	.75620E+01	0.19857E-01
710.51	25.20	52.84	20.60	870.6293	0.86	862.00	20.00	787.4	485.9	30.73	.75620E+01	0.19856E-01
714.47	27.52	55.60	23.03	870.7678	0.86	862.00	20.00	782.4	454.2	30.73	.75620E+01	0.19857E-01
718.43	29.85	58.35	25.47	870.9063	0.86	862.00	20.00	777.3	422.5	30.73	.75620E+01	0.19858E-01
722.39	30.09	59.01	25.82	870.9207	0.86	862.00	20.00	772.3	414.8	30.73	.75620E+01	0.19858E-01
726.35	28.96	58.31	24.81	870.8536	0.86	862.00	20.00	767.3	422.7	30.73	.75620E+01	0.19858E-01
730.31	27.97	57.73	23.93	870.7942	0.86	862.00	20.00	762.4	429.2	30.73	.75620E+01	0.19857E-01
734.27	28.45	58.64	24.52	870.8231	0.86	862.00	20.00	757.4	418.6	30.73	.75620E+01	0.19858E-01
738.24	28.94	59.54	25.12	870.8519	0.86	862.00	20.00	752.4	408.0	30.73	.75620E+01	0.19858E-01
742.20	29.42	60.45	25.72	870.8808	0.86	862.00	20.00	747.3	397.5	30.73	.75620E+01	0.19858E-01
746.16	29.44	60.89	25.85	870.8818	0.86	862.00	20.00	742.4	392.3	30.73	.75620E+01	0.19858E-01
750.12	28.31	60.18	24.84	870.8147	0.86	862.00	20.00	737.4	400.2	30.73	.75620E+01	0.19858E-01

754.08 27.19 59.48 23.83 870.7477 0.86 862.00 20.00 732.4 408.2 30.73 .75620E+01 0.19857E-01

LEG: L6 23.440 IN. D. (INCH) FROM NODE: N11 TO NODE: N13

754.08	27.19	59.48	23.83	870.7477	0.86	862.00	20.00	732.4	408.2	30.73	.75620E+01	0.19857E-01
758.01	26.07	58.78	23.05	870.6812	0.86	862.00	20.00	727.5	416.0	30.73	.75620E+01	0.19857E-01
761.94	24.95	58.08	22.28	870.6146	0.86	862.00	20.00	722.5	423.9	30.73	.75620E+01	0.19856E-01
765.88	23.84	57.37	21.51	870.5480	0.86	862.00	20.00	717.6	431.8	30.73	.75620E+01	0.19856E-01
769.81	22.72	56.67	20.73	870.4814	0.86	862.00	20.00	712.7	439.6	30.73	.75620E+01	0.19856E-01
773.74	22.26	56.62	20.38	870.4537	0.86	862.00	20.00	707.7	440.0	30.73	.75620E+01	0.19855E-01
777.68	21.82	56.61	19.94	870.4280	0.86	862.00	20.00	702.7	440.0	30.73	.75620E+01	0.19855E-01
781.61	22.23	57.43	20.35	870.4523	0.86	862.00	20.00	697.8	430.3	30.73	.75620E+01	0.19855E-01
785.54	23.85	59.48	21.97	870.5490	0.86	862.00	20.00	692.8	406.7	30.73	.75620E+01	0.19856E-01
789.48	25.48	61.52	23.59	870.6456	0.86	862.00	20.00	687.8	383.1	30.73	.75620E+01	0.19857E-01
793.41	25.32	61.78	23.44	870.6362	0.86	862.00	20.00	682.8	380.0	30.73	.75620E+01	0.19856E-01
797.34	24.89	61.77	23.01	870.6105	0.86	862.00	20.00	677.9	380.0	30.73	.75620E+01	0.19856E-01
801.28	24.45	61.75	22.57	870.5847	0.86	862.00	20.00	672.9	380.0	30.73	.75620E+01	0.19856E-01
805.21	24.02	61.74	22.14	870.5590	0.86	862.00	20.00	667.9	380.0	30.73	.75620E+01	0.19856E-01
809.14	23.59	61.72	21.71	870.5333	0.86	862.00	20.00	663.0	380.0	30.73	.75620E+01	0.19856E-01
813.07	22.09	60.63	20.21	870.4437	0.86	862.00	20.00	658.1	392.3	30.73	.75620E+01	0.19855E-01
817.01	20.29	59.24	18.41	870.3364	0.86	862.00	20.00	653.1	408.0	30.73	.75620E+01	0.19855E-01
820.94	18.49	57.86	16.61	870.2291	0.86	862.00	20.00	648.2	423.8	30.73	.75620E+01	0.19854E-01
824.87	16.69	56.47	14.81	870.1218	0.86	862.00	20.00	643.2	439.5	30.73	.75620E+01	0.19853E-01
828.81	14.89	55.08	13.01	870.0146	0.86	862.00	20.00	638.3	455.2	30.73	.75620E+01	0.19853E-01
832.74	15.71	56.32	13.83	870.0635	0.86	862.00	20.00	633.3	440.8	30.73	.75620E+01	0.19853E-01
836.67	17.67	58.71	15.79	870.1804	0.86	862.00	20.00	628.3	413.3	30.73	.75620E+01	0.19854E-01
840.61	18.84	60.30	16.96	870.2502	0.86	862.00	20.00	623.3	394.8	30.73	.75620E+01	0.19854E-01
844.54	15.67	57.54	13.80	870.0615	0.86	862.00	20.00	618.4	426.3	30.73	.75620E+01	0.19853E-01
848.47	12.50	54.78	10.63	869.8727	0.86	862.00	20.00	613.5	457.8	30.73	.75620E+01	0.19852E-01
852.41	9.34	52.02	7.46	869.6841	0.86	862.00	20.00	608.5	489.2	30.73	.75620E+01	0.19851E-01
856.34	7.03	50.12	5.16	869.5469	0.86	862.00	20.00	603.6	510.8	30.73	.75620E+01	0.19850E-01

860.27	6.40	49.91	4.53	869.5095	0.86	862.00	20.00	598.6	513.0	30.73	.75620E+01	0.19849E-01
864.20	5.78	49.70	3.90	869.4721	0.86	862.00	20.00	593.6	515.3	30.73	.75620E+01	0.19849E-01
868.14	5.15	49.49	3.28	869.4348	0.86	862.00	20.00	588.6	517.5	30.73	.75620E+01	0.19849E-01
872.07	4.52	49.28	2.65	869.3974	0.86	862.00	20.00	583.7	519.8	30.73	.75620E+01	0.19849E-01
876.00	3.89	49.06	2.02	869.3600	0.86	862.00	20.00	578.7	522.0	30.73	.75620E+01	0.19849E-01
879.94	3.26	48.85	1.39	869.3226	0.86	862.00	20.00	573.7	524.2	30.73	.75620E+01	0.19848E-01
883.87	2.64	48.64	0.77	869.2852	0.86	862.00	20.00	568.7	526.5	30.73	.75620E+01	0.19848E-01
887.80	2.01	48.43	0.14	869.2479	0.86	862.00	20.00	563.7	528.7	30.73	.75620E+01	0.19848E-01
891.74	2.17	49.01	0.30	869.2574	0.86	862.00	20.00	558.8	521.9	30.73	.75620E+01	0.19848E-01
895.67	3.33	50.60	1.46	869.3266	0.86	862.00	20.00	553.8	503.5	30.73	.75620E+01	0.19848E-01
899.60	4.49	52.18	2.62	869.3958	0.86	862.00	20.00	548.8	485.2	30.73	.75620E+01	0.19849E-01
903.54	5.66	53.77	3.79	869.4650	0.86	862.00	20.00	543.8	466.8	30.73	.75620E+01	0.19849E-01
907.47	6.82	55.36	4.95	869.5342	0.86	862.00	20.00	538.8	448.5	30.73	.75620E+01	0.19850E-01
911.40	7.98	56.94	6.11	869.6034	0.86	862.00	20.00	533.8	430.1	30.73	.75620E+01	0.19850E-01
915.34	9.14	58.53	7.27	869.6726	0.86	862.00	20.00	528.9	411.8	30.73	.75620E+01	0.19850E-01
919.27	10.31	60.12	8.44	869.7418	0.86	862.00	20.00	523.9	393.4	30.73	.75620E+01	0.19851E-01
923.20	9.62	59.84	7.75	869.7007	0.86	862.00	20.00	518.9	396.4	30.73	.75620E+01	0.19851E-01
927.13	9.24	59.88	7.37	869.6783	0.86	862.00	20.00	513.9	395.7	30.73	.75620E+01	0.19851E-01
931.07	9.12	60.18	7.25	869.6713	0.86	862.00	20.00	508.9	392.1	30.73	.75620E+01	0.19850E-01
935.00	8.00	59.48	6.14	869.6049	0.86	862.00	20.00	504.0	400.0	30.73	.75620E+01	0.19850E-01

LEG: L7 23.000 IN. D. (INCH) FROM NODE: N13A TO NODE: N13B

935.00	8.00	59.48	6.14	869.6048	0.90	862.00	20.00	504.0	400.0	30.73	.75620E+01	0.19780E-01
935.05	8.00	59.48	6.13	869.6044	0.90	862.00	20.00	503.9	400.0	30.73	.75620E+01	0.19780E-01

LEG: L8 23.000 IN. D. (INCH) FROM NODE: N13D TO NODE: N13E

935.05	2.11	59.48	1.96	869.2542	0.90	862.00	20.00	436.2	400.0	30.73	.75620E+01	0.19778E-01
936.00	2.00	59.48	2.00	869.2474	0.90	862.00	20.00	434.9	400.0	30.73	.75620E+01	0.19778E-01

TIME = 0.000 (MINS)
EQUIPMENT ID: PUMPIP2 FROM NODE: N05 TO NODE: N06

PUMP
MIN PU MODE (PU = PUMIN)
UPSIDE PRESSURE 5.00 A)(KG
DOWNSIDE PRESSURE 62.04 A)(KG
HEAD DIFFERENTIAL 653.60 (M)
STANDARD FLOW THRU EQUIPMENT 862.0 (M3/HR)
ACTUAL FLOW THRU EQUIPMENT 863.1 (M3/HR)
UPSIDE TEMPERATURE 20.00 (DEG C)
DOWNSIDE TEMPERATURE 20.00 (DEG C)
CURRENT SPEED 0.00 (RPM)
ADIABATIC EFFIC 100.00
POWER REQUIRED 1.34 (MW)
POWER AVAILABLE 1.34 (MW)
PERCENT OPEN SETPOINT 1.000
FREE FLOW CONSTRAINT
UP PRES SETPT/MIN CONSTRAINT 5.0 A)(KG

EQUIPMENT ID: PUMPIP4 FROM NODE: N09 TO NODE: N10

PUMP
MIN PU MODE (PU = PUMIN)
UPSIDE PRESSURE 5.00 A)(KG
DOWNSIDE PRESSURE 48.23 A)(KG
HEAD DIFFERENTIAL 495.84 (M)
STANDARD FLOW THRU EQUIPMENT 862.0 (M3/HR)
ACTUAL FLOW THRU EQUIPMENT 863.5 (M3/HR)
UPSIDE TEMPERATURE 20.00 (DEG C)
DOWNSIDE TEMPERATURE 20.00 (DEG C)
CURRENT SPEED 0.00 (RPM)
ADIABATIC EFFIC 100.00
POWER REQUIRED 1.02 (MW)
POWER AVAILABLE 1.02 (MW)
PERCENT OPEN SETPOINT 1.000
FREE FLOW CONSTRAINT
UP PRES SETPT/MIN CONSTRAINT 5.0 A)(KG

EQUIPMENT ID: PUMPVAD FROM NODE: N01 TO NODE: N02

PUMP

MIN PU MODE (PU = PUMIN)
 UPSIDE PRESSURE 2.00 A)(KG
 DOWNSIDE PRESSURE 44.38 A)(KG
 HEAD DIFFERENTIAL 486.26 (M)
 STANDARD FLOW THRU EQUIPMENT 862.0 (M3/HR)
 ACTUAL FLOW THRU EQUIPMENT 863.7 (M3/HR)
 UPSIDE TEMPERATURE 20.00 (DEG C)
 DOWNSIDE TEMPERATURE 20.00 (DEG C)
 CURRENT SPEED 0.00 (RPM)
 ADIABATIC EFFIC 100.00
 POWER REQUIRED 1.00 (MW)
 POWER AVAILABLE 1.00 (MW)
 PERCENT OPEN SETPOINT 1.000
 FREE FLOW CONSTRAINT
 UP PRES SETPT/MIN CONSTRAINT 2.0 A)(KG

EXTERNAL REGULATOR HYDRAULIC DETAILED REPORT

TIME = 0.000 (MINS)

MASS FLOWRATE BALANCE (ACTUAL CONDITIONS) = 0.000 SLUG/SEC

SYSTEM PACKING RATE (STANDARD CONDITIONS) = 0.000 (M3/HR)

EXTERNAL REGULATOR ID: BINA AT NODE: N13F

DELIVERY

MIN PRES MODE (P = PMIN)
 PRESSURE 2.00 A)(KG
 STANDARD FLOW 862. (M3/HR)
 ACTUAL FLOW 865. (M3/HR)
 TEMPERATURE 20.00 (DEG C)
 CUMULATIVE FLOW THROUGH XRG 0. (M3)
 PRES SETPT/MIN CONSTRAINT 2.00 A)(KG
 CHECK VALVE CONSTRAINT

EXTERNAL REGULATOR ID: SRV AT NODE: N13C

DELIVERY

CLOSED MODE (NO FLOW, Q = 0)
 PRESSURE 4.11 A)(KG

STANDARD FLOW 0. (M3/HR)
ACTUAL FLOW 0. (M3/HR)
TEMPERATURE 20.00 (DEG C)
CUMULATIVE FLOW THROUGH XRG 0. (M3)
PRES SETPT/MIN CONSTRAINT 12.00 A)(KG
CHECK VALVE CONSTRAINT

EXTERNAL REGULATOR ID: VADINAR AT NODE: N01

SUPPLY
MAX FLOW MODE (Q = QMAX)
PRESSURE 2.00 A)(KG
STANDARD FLOW -862. (M3/HR)
ACTUAL FLOW -865. (M3/HR)
TEMPERATURE 20.00 (DEG C)
CUMULATIVE FLOW THROUGH XRG 0. (M3)
FLOW SETPT/MAX CONSTRAINT -862.00 (M3/HR)

TLNET VERSION 5.1

A PROPRIETARY PRODUCT OF SS-I

PAGE 21

TLNET TRANSIENT OUTPUT OPTIONS REPORT

REPORT TYPES:

- 0 = NO REPORT
- 1 = SUMMARY REPORT
- 2 = DETAIL REPORT

*** LEG REPORT OPTIONS

LEG HYDRAULIC REPORT: 2

REPORTING ALL LEGS

*** PUMP REPORT OPTIONS

PUMP HYDRAULIC REPORT: 2

REPORTING ALL PUMPS

*** REGULATOR REPORT OPTIONS

REGULATOR HYDRAULIC REPORT: 1

REPORTING ALL REGULATORS

*** BLOCK VALVE REPORT OPTIONS

BLOCK VALVE HYDRAULIC REPORT: 1

REPORTING ALL BLOCK VALVES

*** CHECK VALVE REPORT OPTIONS

CHECK VALVE HYDRAULIC REPORT: 1

REPORTING ALL CHECK VALVES

*** RESISTANCE REPORT OPTIONS

RESISTANCE HYDRAULIC REPORT: 1

REPORTING ALL RESISTANCES

*** EXTERNAL REGULATOR REPORT OPTIONS

EXTERNAL REGULATOR HYDRAULIC REPORT: 2

REPORTING ALL EXTERNAL REGULATORS

*** TANKAGE REPORT OPTIONS

TANKAGE HYDRAULIC REPORT: 1

REPORTING ALL TANKS

*** BATCH REPORT OPTIONS

BATCH REPORT: 0


*** NODE MASS BALANCE REPORT OPTIONS

NODE MASS BALANCE REPORT: 0

CHAPTER 6 CONCLUSION

6.1 GRAPHICAL ANALYSIS:

TABLE: 5 OPTIMISATION FOR PUMP LOCATIONS.



6.2 For Optimisation:

From the output, the value obtained for the intermediate pumping station: 1 is not optimized location for the BORL pipeline. In the future expansion of the throughput is not possible for the current location of IP: 1 because now the IP: 1, pumping pressure is 62.04Kg/cm². Here the max operating pressure of the line is 63.7 Kg/cm²

(and the design pressure is 70.1 Kg/Cm^2). For optimization and for future expansion the mainline pumping pressure can be increased from 44.38 Kg/cm^2 to 50 Kg/cm^2 , so that IP: 1 chainage will be much forward than current location (say may be from Ch: 350.85Km to Ch: 394.11Km). By relocating the IP: 1, the operating pressure can be much lesser than current fixed pressure (i.e. to 57 Kg/Cm^2).

Now the current pressure can be reduced to 57 Kg/Cm^2 from 62 kg/Cm^2 , so that in future the throughput can handled much more than now (current throughput is $862 \text{ m}^3/\text{Hr}$). There's no need in changing IP: 2 location. And also surge relief valve timings is calculated by TLNet for the shut off/on part.

REFERNCES:

- [1] Henry Liu, Pipeline Engineering, Lewis Publishers, 1970.
- [2] A.P.Moser, Buried Pipe Design, McGraw Hill. 1990.
- [3] Mo Mohitpur, Jason Szabo, Thomas Van Hardeveld, Pipeline Design and Construction: A Practical Approach, ASME Press, 2005.
- [4] C.B. Lester, Hydraulics for Pipeliners, Vol-1, Gulf Publishing Company, 1990.
- [5] Transient Liquid Net Analysis, 5.1 Version Manual, 1984.
- [6] Bharath Oman Refinery Limited Pipeline data's (Job No: 1205 specified by EIL).
- [7] Engineers India Limited web sites.
- [8] E.shashi Menon, Liquid Pipeline Hydraulics, PD Hengineer.com, online course Material.

ANNEXURE

LIST OF CODES AND STANDARDS

In addition to the codes/standards mentioned, the latest edition of the below listed equivalent codes and standards shall also be used for design of proposed pipeline. The listing includes, but is not limited to, the following:

1. Line Pipes

API 5L Specification for Line pipe

API 5L1 Recommended Practice for Railroad Transportation of Line pipe

2. Valves

API 6D Specification for pipeline valves (Steel Gate, Plug, Ball and Check Valves)

ASTM A694 Forgings, Carbon & Alloy steel for Pipe Flanges, Fittings, Valves & parts for High Pressure Transmission Service.

MSS-SP-6 Finishes for Contact Faces of connecting End Flanges of Ferrous Valves and Fittings.

BS 5351 Steel Ball Valves for the Petroleum, Petrochemical and Allied Industries

3. Flanges and Fittings

MSS-SP-44 Steel Pipeline Flanges

ANSI B16.5 Pipe Flanges and Flanged Fittings

ANSI 16.20 Ring-joint Gaskets & Grooves for Steel Pipe Flanges

4. WELDINGS

API 1104 Standard for Welding Pipelines and Related Facilities

AWS A3.0 Welding Terms and Definitions

AWS A5.1 Welding Electrodes

IP Model Code of Safe Practice in the Petroleum Industry parts 3, 6 and 9.